



Railroad Spike over the Stone
at the N.W. Cor. of Section 28,
Washington, Twp.

Sec. 28.
Washington Twp.



Scale:

$$\frac{1}{100}$$


Being a parcel of land situate in the Northwest quarter of Section 28, T-6-S, R-5-E, Washington Township, Auglaize County, Ohio and more particularly described as follows:

Commencing at a railroad spike found a stone at the northwest corner of said Northwest quarter of said Section 28: thence S 00°30'00" E with the west line of said Northwest quarter (passing through a concrete monument found at 703.77 feet and 1115.04 feet), 1233.00 feet to a 5/8 inch rebar set and the PLACE OF BEGINNING thence continuing S 00°30'00" E with said west line of said Northwest quarter, 50.00 feet to a 5/8 inch rebar set; thence N 88°41'00" E, 676.90 feet to a 5/8 inch rebar set; thence N 00°30'00" W, 50.00 feet to a 5/8 inch rebar set; thence S 88°41'00" W, 676.90 feet to the PLACE OF BEGINNING containing 0.777 acre more or less and subject to all legal easements of record.

5/8" Rebar Being The
PLACE OF BEGINNING

588° 41' W 676.90'

5/8' Ref
Set.

32.10
N88.41'E

500° 30' E

$N 88^{\circ} 41' E \ 676.90'$

50.00
N/00=30'W

5/8" Rebar
Set.

5/8" Rebar Set

N 00° 30' W
430.07.

7.00 Acres
Surveyed by Clayton Stimmel
1-16-71.

Now owned by Rytec Investments

588° 41' W 709.00'

Signed: _____ Date _____

for political S. D. of: _____ Date _____

Signed: _____ Date _____

Signed: _____ Date _____

Richard D

LS 6470

Client Aztec Investment % Richard Cook
County Huglaize Twp. Washington Sec. 28
Drawn by Jim Endrick Scale 1" = 100' Drwg. No. H 810
Checked by _____ Date _____
Sheet 1 of 1 (T 6 S; R 5 E)

(T 6 S:R 5 E)