

THIS PLAT IS RECORDED IN
SURVEY BOOK "I", PAGE 67, IN
THE DOUGLASS COUNTY ENGINEER'S
OFFICE.

ATTEST: *John W. Jauert*
JOHN W. JAUERT
PROFESSIONAL
SURVEYOR NO. 6920

KAN

Jauert
ASSOCIATES

Surveying
AND LAND CONSULTING

RT. 3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

I-67


Client TELEPHONE SERVICE CO.

County DOUGLASS Township PUSKETTA

Section 5 T. 6 S., R. 6 E. Drwg. No. 90-520

Drawn By J. JAUERT Date FEB. 1990

Scale 1"=100' Sheet 1 of 2



Being an easement for the Telephone Service Company located in the Northwest Quarter of Section 5, Town 6 South, Range 6 East, Pusheta Township, Auglaize County, Ohio and being further described as follows:

Commencing at a monument box at the Northwest corner of said Northwest Quarter of said Section 5;

thence S.89°13'18"E. along the North line of said Northwest Quarter and the existing centerline of County Road 140 (Canning Factory Road), a distance of 1,102.72 feet to a point at the intersection of County Road 140 and the tangent of the existing centerline of County Road 133-A (Hardin Pike);

thence S.05°37'22"W. along the tangent of the centerline of County Road 133-A and the centerline of County Road 133-A, a distance of 1,206.64 feet to the grantor's Southeast corner;

thence N.89°22'38"W. along the grantor's South line, a distance of 104.11 feet to a point which is the PLACE OF BEGINNING for the tract of land herein described;

thence continuing N.89°22'38"W. along the grantor's South line a distance of 10.00 feet to a point;

thence N.02°14'09"E. a distance of 101.80 feet to a point;

thence N.64°22'38"W. a distance of 114.79 feet to a point;

thence N.58°09'01"W. a distance of 204.63 feet to a point;

thence Northwesterly along a curve to the right with a radius of 994.93 feet, a distance of 327.11 feet to a point on the grantor's Northerly line, the chord to said curve bears N.48°57'34"W., a distance of 325.64 feet;

thence S.89°07'40"E. along the grantor's North line a distance of 13.18 feet to a point;

thence Southeasterly along a curve to the left with a radius of 984.93 feet, a distance of 315.29 feet to a point, the chord to said curve bears S.49°12'24"E., a distance of 313.94 feet;


thence S.58°09'01"E. a distance of 204.12 feet to a point;

thence S.64°22'38"E. a distance of 120.82 feet to a point;

thence S.02°14'09"W. a distance of 108.09 feet to a point on the grantor's South line, which was the true PLACE OF BEGINNING.

Containing in all 0.17 acre of land. Previous deed reference: Volume 265, page 160. This plat is recorded in Survey Book "I", page 67, in the Auglaize County Engineer's office.

ATTEST;


John W. Jauert
Professional Surveyor No. 6920



Kau

Jauert
ASSOCIATES



Surveying
AND LAND CONSULTING

RT.3 BOX 449 WAPAKONETA, OHIO 45895
PH. (419) 738-8962

I-68

Client TELEPHONE SERVICE CO.
County AUGLAIZE Township PUSHETA
Section 5 T. 6 S., R. 6 E. Drwg. No. 90-520
Drawn By _____ Date FEB. 1990
Scale _____ Sheet 2 of 2