

The following described tract of land is part of the Northwest Quarter of the Northwest Quarter of Section 8, Town 7 South, Range 4 East, German Township, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is at an iron pin (0.D.O.T.) over the stone found at the Northwest corner of the Northwest Quarter of Section 8, German Township, and in the intersection of the centerlines of State Route 364 and County Road 70 (Lock Two Road);

thence S.88°41'20"E. along the centerline of County Road 70 and the North line of the Northwest Quarter of Section 8 German Township, a distance of 311.06 feet to a P.K. nail set, passing thru an iron pin set for reference at 25.00 feet in the South right-of-way line of County Road 70;

thence S.00°30'W., parallel to the centerline of State Route 364 and the West line of the Northwest Quarter of Section 8, German Township, a distance of 180.00 feet to an iron pin set;

thence N.88 41'20 W. a distance of 311.06 feet to a P.K. nail set, passing thru an iron pin set for reference at 281.06 feet in the East right-of-way line of State Route 364;

thence $\rm N.00^{\circ}\,30'E$. along the centerline of State Route 364 and the West line of the Northwest Quarter of said Section 8, a distance of 180.00 feet to the iron pin which was the true PLACE OF BEGINNING.

Containing in all 1.285 acre of which 0.285 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 157, page 410. This plat is recorded in Survey Book "I", page 44, in the Auglaize County Engineer's Office.

JOHN
W.
JAUERT
6920

ONAL SURGER

ATTEST;_

John W. Jauert

Professional Surveyor No. 6920



County Augustie Township Sermine

Section B. T. T. S., R. A. E. Drwg. No. 90-590 A

Drawn By S. Sauget Date 17-8-90

Scale 1"= 100' Sheet 1 of 1