

The following described tract of land is part of the Southwest Quarter of Section 35, Town 7 South, Range 4 East, Jackson Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a P.K. nail found at the West Quarter corner of Section

35, Jackson Township and in the centerline of State Route 66; thence N.89°51'38"E. along the East-West half Section line (as per survey by Allen & Associates, June, 1984). a distance of 952.90 feet to an iron pin found;

thence S.01°21'07"W. a distance of 869.11 feet to an iron pin set which is the PLACE OF BEGINNING for the tract of land herein described; thence continuing S.01°21'07"W. a distance of 50.00 feet to an iron pin

thence N.89°46'46"W. a distance of 205.97 feet to an iron pin found; thence N.01°21'07"E. a distance of 50.00 feet to an iron pin set; thence S.89°46'46"E. a distance of 205.97 feet to an iron pin set, which was the true PLACE OF BEGINNING.

Containing in all 0.236 acre and is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 89, page 291. This plat is recorded in Survey Book "I", page 297, in the Auglaize County Engineer's Office.



ATTEST: John W. Jauert Professional Surveyor No. 6920



PH. (419) 738-8962

<u>DUGLAIZE</u> Township <u>JACKSON</u> T. ____ S. , R. ___ E. Drwg. No. 91-592-A 10-01-5 Date TRBUAC _Sheet_____ of __

Client MEYER SURVEY