

thence S.00°07'54"E. a distance of 1,334.47 feet to an iron pin set,

passing thru an iron pin set for reference at 20.00 feet in the South rightof-way of Township Road 120;

thence S.89°42'38"W. along the South line of the Northeast Quarter of the Northwest Quarter of Section 16, a distance of 665.21 feet to an iron pin set;

thence N.00°07'54"W. along the West line of the Northeast Quarter of the Northwest Quarter of Section 16, a distance of 1,334.03 feet to a R.R. spike set, passing thru an iron pin set for reference at 1,314.03 feet in the South right-of-way line of Township Road 120;

thence N.89°40'23"E. along the centerline of Township Road 120 and the North line of the Northwest Quarter of Section 16, a distance of 665.21 feet to the R.R. spike which was the true PLACE OF BEGINNING.

Containing in all 20.375 acre of which 0.305 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume 205, page 66. This plat is recorded in Survey Book "I", page 404, in the Aughaize County Engineer's ODD TO THE TOTAL OF THE TOTAL O Office.



OF

RT.3 BOX 449 WAPAKONETA, OHIO 45895

PH.(419)738-8962

T- 404

Client BYRON RUCK

County DUGLAIZE Township PUSLETA

Section \ CO I. CO S., R. CO E. Drwg. No. 91-

Drawn By 3. SAUERT Date DEPT. 1991

Scale 1=300 $_$ Sheel $_$ $_$ of $_$ $_$