
This Survey is Recorded in Survey Book "I ' Page430 Auglaize County Engineer's Office North line of the Southwest Quarter, N Northeast Corner of the Southwest Quarter. Section 24, Moulton Township and centerline of C.R. #166, Infirmary Road Site Location IN? Vol 241 Vol OR 86 SITE Pg Pg 182 N. 87°-15'-14" E Vol 145 #117A Pg 150 937.34 Section 24, Moulton Township, Road Auglaize, County, Ohio Centerline of Township 7 Acres 4 PLACE Tangent Table 1.34 Acres Right-of-Way S. 89°-23'-00" W. 143.65 327.05 S. 00°-37'-00" E. Attest: Ila 121 30.00 N. 82°-47'-00" W. Ted K. Schnell 131 Iron Pin Professional Engineer N. 00°-37'-00" W. 370.00 At 34.23 [4] Professional Surveyor [8] 104.15 N. 04°-04'-55" W. [5] 109.74 N. 07°-07'-40" W. [6] [7] 168.48' ·Vol 252 N. 13°-22'-40" W. [7] 3632 N. 24°-20'-55" W. 47.63 [8] Vol OR 6 [6] Pg 6655 Bearing = Legend Vol OR 43 Pg 152 Railroad Spike Found S. 89°-23'-00" Iron Pin Set Iron Pin Found Pin At 25.24" OR 136 P.K. Nail Set OR 4 130 P.K. Nail Found - Vol 211 -100 9 Monument, Box Pg 756 Iron Pin At 25.06 #II7A [3] Centerline of County Road Road #158 Scale Centerline of Vol OR 13 Township South line of the Vol 204. 93 Southwest Quarter Pg 526 Section 24 Signature by a representative of the Auglaize County Regional Signature by a representative of the County Health Dept. denotes Planning Commission denotes approval of this plat. compliance with Health Regulations. Signed: _ Signed: Signature by a representative of City with 3 mile limit jurisdiction Signature by a representative of the County Engineer's Dept. or Twp. Trustees or Village with zoning jurisdiction denotes denotes that this plat meets tax map plat requirements. approval of this plat. Signed: __ for political S.D. of: Client Twp. Moulton Sec. _ Auglaiz: Kevin County _ Scale Snown Drawn by _ Checked by Date T-430 Sheet _ of___

Ted Kevin Schnell

Registered Professional Engineer Registered Professional Surveyor

Civil Engineering Land Surveying

R.R. No. 3 11873 Glymcood Road Wapakoneta, Ohio 45895 phone - (419) 738- 4758



county Auguste township Mourton section ZA T- 5-S, R- 5-E drawn by Kaun date 1/3/97 checked by GREG sheet Z of Z

The following described tract of land is situated in the Southwest Quarter of Section 24, Moulton Township, Town-5-South, Range-5-East, Auglaize County, Ohio, and is more particularly described as follows:

COMMENCING at an Auglaize County Monument Box located at the Northeast Corner of the Southwest Quarter of Section 24, Moulton Township, Town-5-South, Range-5-East, Auglaize County, Ohio;

THENCE with a bearing of S. 00°-37'-00" E. along the East line of the Southwest Quarter of said Section 24 for a distance of 458.40 feet to a point and the PLACE OF REGINNING:

THENCE continuing with a bearing of S. 00°-37'-00" E. along the East line of the Southwest Quarter of said Section 24 for a distance of 1,293.75 feet to an iron pin (found);

THENCE with a bearing of S. 89°-23'-00" W. for a distance of 143.65 feet to an iron pin (found);

THENCE with a bearing of S. 00°-37'-00" E. for a distance of 327.05 feet to a P.K. Nail/Shiner located on the centerline of County Road #158, Glynwood Road, and passing thru an iron pin (found) on the Northerly right-of-way line of said road at a distance of 301.81 feet:

THENCE with a bearing of N 82°-47'-00" W. along the centerline of County Road #158, Glynwood Road, for a distance of 30.00 feet to a P.K. Nail/Shiner (found) at the P.C. of a Curve to the left;

THENCE along the centerline of County Road #158, Glynwood Road, following a curve to the left for an arc distance of 118.16 feet, of which a chord bears N. 88°-44'-04" W. for a distance of 117.95 feet to a P.K. Nail/Shiner (found), said curve to the left having the following curve data: Delta \triangle = 25°-54'-42", Radius (R) = 568.82 feet, and Tangent (T) = 130.86 feet;

THENCE with a bearing of N. 00°-37'-00" W. for a distance of 370.00 feet to an iron pin (set), and passing thru an iron pin (set) on the Northerly right-of-way line of said road at a distance of 25.06 feet;

THENCE with a bearing of S. $89^{\circ}-23^{\circ}-00^{\circ}$ W. for a distance of 311.36 feet to an iron pin (set);

THENCE with a bearing of S. 00°-37'-00" E. for a distance of 436.78 feet to a P.K. Nail/Shiner located on the centerline of Township Road #117A, Buckland River Road, and passing thru an iron pin (set) on the Northerly right-of-way line of said road at a distance of 406.65 feet;

THENCE with a bearing of S. 84°-04'-15" W. along the centerline of Township Road #117A for a distance of 733.57 feet to an iron pin (found);

THENCE with a bearing of N. 04°-04'-55" W. along the centerline of Township Road #117A for a distance of 104.15 feet to a Railroad Spike (found);

THENCE with a bearing of N. 00°-46'-30" W. along the centerline of Township Road #117A for a distance of 675.68 feet to a Railroad Spike (found);

THENCE with a bearing of N. 07°-07'-40" W. along the centerline of Township Road #117A for a distance of 109.74 feet to a Railroad Spike (found);

THENCE with a bearing of N. 13° -22'-40" W. along the centerline of Township Road #117A for a distance of 168.48 feet to a P.K. Nail (found);

THENCE with a bearing of N. $24^{\circ}-20'-55"$ W. along the centerline of Township Road #117A for a distance of 47.63 feet to a P.K. Nail/Shiner (set);

THENCE with a bearing of N. 36°-53'-21" E. for a distance of 776.62 feet to an iron pin (found), and passing thru an iron pin (set) on the Easterly right-of-way line of Township Road #117A at a distance of 34.23 feet;

THENCE with a bearing of N. 87°-15'-14" E. for a distance of 937.84 feet to a point on the East line of the Southwest Quarter of Section 24, Moulton Township, said point being the original PLACE OF BEGINNING.

CONTAINING IN ALL 44.777 acres of land subject to 1.34 acres being previously dedicated for highway purposes. The above described tract of land is also subject to all other legal easements, reservations, or restrictions of public knowledge, if any, upon said premises. Previous Deed References is recorded in Volume 199, Page 245, Auglaize County Recorder's Office. The survey and description for this tract of land is also recorded in Survey Book " I ", Page 430 , in the Auglaize County Engineer's Tax Map