

The following described tract of land is part of the Northwest Quarter of the Northwest Fractional Quarter of Section 19, Town 4 South, Range 5 East, Logan Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a P.K. nail found in the center of an obliterated concrete corner post at the Northwest corner of the Northwest Fractional Quarter of Section 19;

thence S.00°39'09"W. along the West line of the Northwest Fractional Quarter of Section 19, a distance of 1,000.36 feet to an iron pin set, which is the PLACE OF BEGINNING for the tract of land herein described;

thence S.89°30'E., parallel to the centerline of County Road 228 (Deep Cut Road), a distance of 156.11 feet to an iron pin set;

thence S.00°39'09"W., parallel to the West line of the Northwest Fractional Quarter of Section 19, a distance of 309.03 feet to a R.R. spike set, passing thru an iron pin set for reference at 279.03 feet in the North right-of-way line of County Road 228;

thence N.89°30'W. along the centerline of County Road 228, a distance of 156.11 feet to an iron pin set;

thence N.00°39'09"E. along the West line of the Northwest Fractional Quarter of Section 19, a distance of 309.03 feet to the iron pin which was the true PLACE OF BEGINNING.

Containing in all 1.10 acre of which 0.10 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume OR 100, page 244. This plat is recorded in Survey Book "I", page 45, in the Auglaize County

Engineer's Office.

ATTEST:

John W. Jauert

Professional Surveyor No. 6920

AND LAND CONSULTING

RT.3 BOX 449 WAPAKONETA, OHIO 45895

PH. (419) 738-8962

I- 445

Client ARCISIE DAWMILLER

County AUGLAIZE Township LOGAN

Section 19 I. A.S., R. S. E. Drwg. No. 92-699

Drawn By S. SAUERT Date APRIL 1992

Scale 1=200 Sheet 1 of 1