

The following described tract of land is part of the Northwest Quarter of Section 10, Town 6 South, Range 8 East, Goshen Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box at the Northeast corner of the Northwest Quarter of Section 10 and in the centerline of Township Road 130 (Goshen Road);

thence S. 89°52'50"W. along the centerline of Township Road 130 and the North line of the Northwest Quarter of Section 10, a distance of 349.11 feet to a P.K. nail set which is the PLACE OF BEGINNING for the tract of land herein described;


thence S. 00°04'06"W. a distance of 503.00 feet to an iron pin set, passing thru an iron pin set for reference at 20.00 feet in the South right-of-way line of Township Road 130;

thence S. 89°52'50"W., parallel to the centerline of Township Road 130 and the North line of the Northwest Quarter of Section 10, a distance of 590.00 feet to an iron pin set;

thence N. 00°04'06"E. a distance of 503.00 feet to a R.R. spike over a stone found;

thence N. 89°52'50"E. along the centerline of Township Road 130 and the North line of the Northwest Quarter of Section 10, a distance of 590.00 feet to the P.K. nail which was the true PLACE OF BEGINNING.

Containing in all 8.167 acre of which 0.27 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any of record or in use on said premises. Previous deed reference: Volume OR 22, page 656. This plat is recorded in Survey Book "I", page 450, in the Auglaize County Engineer's Office.



ATTEST: *John W. Jauert*  
John W. Jauert  
Professional Surveyor No. 6920

**Jauert**  
ASSOCIATES

**Surveying**  
AND LAND CONSULTING

RT. 3 BOX 449 WAPAKONETA, OHIO 45895  
PH. (419) 738-8962

Client BARNES-MANCHESTER

County AUGLAIZE Township GOSHEN

Section 10 T. 6 S., R. 8 E. Drwg. No. 92-680

Drawn By J. JAUBERT Date MARCH 1992

Scale 1" = 200' Sheet 1 of 1