



DESCRIPTION FOR AREA AROUND TREATMENT PLANT

The following described tract of land is part of the Southeast Quarter of Section 18, Town 5 South, Range 7 East, Union Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a corner stone in the East line of Section 18, Union Township, on the North Corporation line of the Village of Uniopolis, said line being the East-West Quarter Section line of Section 18;

thence West along said Quarter Section line, a distance of 1,321.69 feet to a 6" dia. steel corner post found, passing thru an iron pipe at 659.88 feet;

thence S.01°34'10"W. along the East line of the Arrowhead Subdivision, a distance of 691.45 feet to a R.R. spike found in the centerline of State Route 67;

thence S.82°42'W. along the centerline of State Route 67, a distance of 411.24 feet to a P.K. nail set, which is the PLACE OF BEGINNING for the tract of land herein described;

thence S.00°57'30"W. a distance of 121.07 feet to an iron pin set, passing thru an iron pin set for reference at 30.31 feet in the South right-of-way line of State Route 67;

thence N.89°02'30"W. a distance of 41.18 feet to an iron pin set;


thence S.01°02'15"W. a distance of 187.69 feet to an iron pin set;

thence S.89°28'38"W. a distance of 212.15 feet to an iron pin set;

thence N.00°57'30"E. along the East side of a 15.21 acre tract of land as described in Deed Volume 202, page 67, a distance of 277.44 feet to a point, passing thru an iron pin found for reference at 277.15 feet and passing thru an iron pin set for reference at 247.13 feet in the South right-of-way line of State Route 67;

thence N.82°42'E. along the centerline of State Route 67, a distance of 256.17 feet to the P.K. nail, which is the true PLACE OF BEGINNING.

Containing in all 1.525 acre of which 0.18 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume OR 112, page 6. This plat is recorded in Survey Book "I", page 728, in the Auglaize County Engineer's Office.



ATTEST: John W. Jauert, PS
Auglaize County Engineer's Office

Signature by a representative of the County Hecompliance with Health Regulations. Signed:	alth Dept. denotes Date	Planning Commiss	esentative of the Auglai ion denotes approval of	this plat.
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date		
	County	CAUERT CRAWFORD	Twp. Union Scale Date De	Sec. \B Drwg. No.



DESCRIPTION FOR EASEMENT AREA BEHIND TREATMENT PLANT

The following described tract of land is part of the Southeast Quarter of Section 18, Town 5 South, Range 7 East, Union Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a corner stone in the East line of Section 18, Union Township, on the North Corporation line of the Village of Uniopolis, said line being the East-West Quarter Section line of Section 18;

thence West along said Quarter Section line, a distance of 1,321.69 feet to a 6" dia. steel corner post found, passing thru an iron pipe at 659.88 feet;

thence S.01°34'10"W. along the East line of the Arrowhead Subdivision, a distance of 691.45 feet to a R.R. spike found in the centerline of State Route 67;

thence S.82°42'W. along the centerline of State Route 67, a distance of 411.24 feet to a P.K. nail set;

thence S.00°57'30"W. a distance of 121.07 feet to an iron pin set, passing thru an iron pin set for reference at 30.31 feet in the South right-of-way line of State Route 67;

thence N.89°02'30"W. a distance of 41.18 feet to an iron pin set;

thence S.01°02'15"W. a distance of 187.69 feet to an iron pin set, which is the PLACE **OF BEGINNING** for the tract of land herein described;


thence S.29°34'02"W. a distance of 234.06 feet to a point;

thence N.89°02'30"W. a distance of 100.00 feet to a point;

thence N.00°57'30"E. along the East line of a 15.21 acre tract of land as described in Deed Volume 202, page 67, a distance of 200.00 feet to an iron pin set;

thence N.89°28'38"E. a distance of 212.15 feet to an iron pin set, which was the true **PLACE OF BEGINNING**;

Containing in all 0.723 acre and being subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed reference: Volume OR 112, page 6. This plat is recorded in Survey Book "I", page 728, in the Auglaize County Engineer's Office.



ATTEST: Volume W. Jauert, PS
Anglaize County Engineer's Office

Signature by a representative of the County Hea compliance with Health Regulations. Signed: I	-	Flanning Commissi	esentative of the Augl on denotes approval o	
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: for political S.D. of: Date		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date		
	County S. S. Checked by S.	LAIZE SOUTET CRAWFORD	Scale Date	Sec. 18 Dec. 1993 (T 5 S; R 7 E)