

8" Wood Post @
Center of Sec.
16, Wayne, Twp.



Scale:

1"=60'


DESCRIPTION

Being a parcel of land situate in the ^{EAST} Southwest quarter of Section 16, T-5-S, R-8-E, Wayne Township, Auglaize County, Ohio and more particularly described as follows:

BEGINNING at a railroad spike found at the southwest corner of said Southeast quarter of said Section 16; thence N 89°42'10" E with the south line of said Southeast quarter (also the centerline of State Route 67), 229.00 feet to a PK nail set; thence N 00°00'00" E, 162.00 feet to a 5/8 inch rebar set; thence S 89°42'10" W, 111.00 feet to a 5/8 inch rebar set; thence N 00°00'00" E, 113.00 feet to a 5/8 inch rebar set; thence S 89°42'10" W, 118.00 feet to a 5/8 inch rebar set on the west line of the east half of said Section 16; thence S 00°00'00" W with said west line, 275.00 feet to the PLACE OF BEGINNING containing 1.158 acres more or less and subject to all highways and other legal easements of record.



Bearings Used from
Previous Survey
Sec. 16, Wayne Twp.



Deed Ref.
Vol 232, Pg. 531,

Right of Way Line

Copped Nail

30.0'

1.157 ACRES
Survey includes
Residence

Signature by a representative of the County Health Dept.
denotes compliance with Health Regulations.

Signed: _____ Date: _____

Signature by a representative of the Auglaize County Regional
Planning Commission denotes approval of this plat.

Signed: _____ Date: _____

Signature by a representative of City with 3 mile limit juris-
diction or Twp. Trustees or Village with zoning jurisdiction
denotes approval of this plat. Signed: _____

for political S. D. of: _____ Date: _____

Signature by a representative of the County Engineer's Dept.
denotes that this plat meets tax map plat requirements.

Signed: _____ Date: _____

Richard D. Morrissey

for

LS 6470

Client Sam Sutherland

County Auglaize Twp. Wayne Sec. 16

Drawn by Jim Emrick Scale 1"=60' Drwg. No. _____

Checked by _____ Date 5-9-87

Sheet 1 of 1 5-70 (T 5 S; R 8 E)