
## SEC 24 T. 6-S R-5-E WASHINGTON TOWNSHIP

M= I.P. FOUND

OF I.P. SET

B = R.R SPIKE SET



## 0.50 Ac. TO BE TRANSFERED TO THE ADJACENT 1.0 AC.

Being 0.50 Acre located in the northeast quarter of Section 24, Town 6-S, Range 5-East, Washington Township, Auglaize County, Ohio and being further described as follows:

Commencing at an iron bar located at the southeast corner of the northeast quarter of Section 24;

Thence South  $89^{\circ}$  00' West along the half section line of Section 24 and the centerline of Headapohl Road TR # 106, a distance of 1530.98 feet to a railroad spike and the PLACE OF BEGINNING for the parcel herein described.

Thence continuing South 89° 00' West, a distance of 50.00 feet;

Thence North 01° 00' West, a distance of 264.00 feet;

Thence South 89° 00' West, a distance of 165.00 feet;

Thence North 01° 00' West, a distance of 40.00 feet;

Thence North 89° 00' East, a distance of 215.00 feet;

Thence South  $\mathrm{Ol}^{\,\mathrm{O}}$  00° East, a distance of 304.00 feet to the PLACE OG BEGINNING.

Containing in all 0.50 Acre and being subject to all legal easements and rights-of-way of record.

Survey and description prepared by Thomas W. Steinke, Registered Surveyor # 6177, this 4th day of May, 1992