		S RICHARD D.		
Iron Pin @ 5 90°00'00"8 NW Corner NW 4 Sec. 3	PCR 200 E, 2668.77' NW/4 Sec. 169.248	3 SURVE	VE Corner NW 4 Sec. 3	Scale 79 80 00 80 00 80 00 80 00 80 00 80 80 80
P.O.B. PARCEL Nº 1	÷. ∰		(ો
Stone @	18'35"E, 24 N. Line SW /4 S	ec. 3	NE Corner SW1/2 Sec. 3 5/3" Rebar (Set)	9.77
N 89°54' 15"E, 320.00	.00′	PARCEL Nº 78.806 Acre,	L C	8'95" W, 132
SW Corner N's SW 4Sec. 3 N 89°	N'2 SW'4 Sec	2661.88' - 3 89° 49' 25" E	SE Corner N'x SW'4 Sec.3 5/6" Rebar (Set) , 1330.94'	0.000
\mathcal{E}_{k}^{\prime} (Set) \mathcal{E}_{k}^{\prime} 3	W. Line E/2 8/2 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8	PARCE 40.562		DO° 08' 45" W, 1328.77' -
SW Corner SW Corner Sw'/4 Sec. 3 Sec. 3 N 89° 50' 15" W, 1326	Sorner 0 0 0 0 0 0 0 0 0	(S.Line S) K nail (Set) N 39° 50'15" W	Tran Pine	S 00°
ature by a representative of the County Hebres compliance with Health Regulations.	Pla	nature by a representative onling Commission denotes ned:	approval of this plat.	Regional
ature by a representative of City with 3 mile ion or Twp. Trustees or Village with zoning jotes approval of this plat. Signed:	iurisdiction Sign	nature by a representative otes that this plat meets tanded:	k map plat requirements	r's Dept.
CUCK and MORRISEY, INC. CONSULTING ENGINEERS & SURVEYORS LIMA, OHIO 45805 TELEPHONE 228-1735 - AREA CODE 419 2807 CHAPEL HILL DRIVE	Client Harry W County Abgle Drawn by Checked by Sheet J of	Scale /": Da	\left\ Sec. 3 400' Drwg. No	

DESCRIPTION PARCEL NO. 1

Being a part of the north half of the Southwest quarter of Section 3, T-5-8, R-4-E, Salem Township, Auglaize County, Ohio and more particularly described as follows:

BEGINNING at a stone found at the northwest corner of said Southwest quarter of said Section 3; thence S 89°48'35" E with the north line of said Southwest quarter (passing through a 5/8 inch rebar set at 25.00 feet), 2667.49 feet to a 5/8 inch rebar set at the northeast corner of said Southwest quarter; thence S 00°08'45" W with the east like of said Southwest quarter, 1328.77 feet to a 5/8 inch rebar set at the southeast corner of the north half of said Southwest quarter; thence N 89°49'25" W with the south line of said north half of said Southwest quarter (passing through a 5/8 inch rebar set at 1330.94 and at 2636.88 feet), 2661.88 feet to a PK hail set at the southwest corner of said north half of said Southwest quarter; thence N 00°05'45" W with the west line of said Southwest quarter (also the centerline of C.R. 41-A), 531.42 feet to a PK nail set; thence N 89°54'15" E (passing through a 5/8 inch rebar set at 25.00 feet), 320.00 feet to a 5/8 inch rebar set; thence N 00°05'45" W, 340.00 feet to a 5/8 inch rebar set; thence S 89°54'15" W (passing through a 5/8 inch rebar set at 295.00 feet), 320.00 feet to a PK nail set on the west line of said Southwest quarter; thence N 00°05'45" W with said west line (also the centerline of C.R. 41-A), 458.00 feet to the PLACE OF BEGINNING containing 78.806 acres more or less and subject to all highways and other legal easements of record.

DESCRIPTION PARCEL NO. 3

Being the east half of the south half of the Southwest quarter of Section 3, T-5-S, R-4-E, Salem Township, Auglaize County, Dhio and more particularly described as follows:

BEGINNING at an iron pin found at the southeast corner of said Southwest quarter of said Section 3; thence N 89°50'15" W with the south line of said Southwest quarter (also the centerline of T.R. 190), 1328.14 feet to a PK nail set at the southwest conner of said east half of said south half of said Southwest quarter; thence N 00°01'30" E with the west line of said east half of said south half of said Southwest quarter (passing through a 5/8 inch rebar set at 20.00 feet), 1329.10 feet to a 5/8 inch rebar set at the northwest corner of said east half of said south half of said Southwest quarter; thence S 89-49'25" E with the north line of the south half of said Southwest quarter, 1330.94 feet to a 5/8 inch rebar set at the northeast corner of said south half of said Southwest quarter; thence S 00°08'45" W with the east line of said Southwest quarter (passing through a 5/8 inch rebar set at 1308.77 feet), 1328.77 feet to the PLACE OF BEGINNING containing 40.562 acres more or less and subject to all highways and other legal easements of record.

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date		Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date		
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date		
KUCK and MORRISEY, INC. CONSULTING ENGINEERS & SURVEYORS LIMA, OHIO 45805 TELEPHONE 228-1735 - AREA CODE 419 2807 CHAPEL HILL DRIVE	County	Twp. Salem Sec. 3 PDM Scale Drwg. No. Tdm Date 7/15/91 of 3 D-156 (T-5-S:R-4-E)		