

LEGEND

- "A" = IRON BAR IN MONUMENT BOX AT S.W. COR. ~ SEC. 29,
- "B" = " " " " " " " " S.E. COR ~ SEC. 29,
- "C" = " " " " " " " " W. 1/4 POST ~ SEC. 29,
- "D" = IRON PIPE FOUND FROM SURVEY BY CLAYTON STIMMEL DATED 30 JAN. 1966,
- "E" = IRON PIPE FOUND FROM STIMMEL SURVEY TO BE 0.20' SOUTH OF S. LINE OF SEC. 29 (MEASUREMENTS ARE TO THE CORNER & NOT TO PIPE,
- "F" = IRON BAR FROM SURVEY BY K. SCHNELL DATED 30 JUNE 1990,
- "G" = 5/8" IRON BAR FROM PRIOR SURVEY BY THIS SURVEYOR DATED 28 AUGUST 1991,
- "H" = P.K. NAIL FOUND FROM AUGUST 28TH SURVEY,
- I = MINE SPIKE " " " " " "

S. LINE ~ S.W. 1/4 ~ SEC. 29 & GLYNWOOD ~ NEW KNOXVILLE RD.

N. 02° 05' 10" W. ~ 2637.87

"C" 2215.02
"H" 272.85
"A" 150.00

GEORGE FISHER
VOL 223, PG. 463

N. 88° 09' 43" E.

557.14'

4.243
ACRES

S. 88° 08' 48" W.

310.40'

1.069
ACRES

N. 02° 05' 10" W.
150.00'

"G"

310.40'

S. 88° 08' 48" W. ~

SOUTH LINE SECTION 29

227.00

S. 00° 34' 48" W.
423.08'

"D"

"F"


"B"

N



SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR
NO 5372

LOCATION
SKETCH



SECTION 29

JONES SURVEY
PART OF THE S.W. 1/4 OF SECTION
29, TOWN 5 SOUTH, RANGE 5
EAST (MOULTON TOWNSHIP, AUG-
LAIZE COUNTY, OHIO.

JULY 24, 1992

SCALE 1"=100'

GORDON L. GEESLIN

LAND SURVEYOR

810 EAST MARKET STREET

CELINA, OHIO

PHONE (419) 586-6155



PERMANENT
PARCEL No. _____

Part of: _____ Sec. _____ T _____ R _____ Township

Grantor: _____ Area Retained: _____ Acres

Grantee: _____ Area Transferred: _____ Acres

Deed References: _____

APPROVALS

AGENCY
DATE

Board of Health

County Sanitary Engineer

County Engineer

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

July 24, 1992

JONES SURVEY DESCRIPTION

Being a parcel of land situated in Moulton Township, Auglaize County, Ohio, in the southwest quarter of Section 29, Township 5 South, Range 5 East. Being more particularly described as follows:

Commencing at an iron bar in a monument box at the southwest corner of said Section-24-

Thence, north 02°05'10" west, along the west line of the southwest quarter of said Section 29 and the centerline of Glynwood-New Knoxville Road, a distance of one hundred fifty (150.00) feet to a mine spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing, north 02°05'10" west, along the last described line, a distance of two hundred seventy-two and 85/100 (272.85) feet to a "P.K." nail-

Thence, north 88°09'43" east, a distance of five hundred fifty-seven and 14/100 (557.14) feet to a 3/4 inch iron pipe-

Thence, south 00°34'48" west, a distance of four hundred twenty-three and 08/100 (423.08) feet to a point in the south line of said Section 29-

Thence, south 88°08'48" west, along the south line of said Section 29, a distance of two hundred twenty-seven and 06/100 (227.06) feet to a 5/8 inch iron bar-

Thence, north 02°05'10" west, a distance of one hundred fifty (150.00) feet to a 5/8 inch iron bar-

Thence, south 88°08'48" west, a distance of three hundred ten and 40/100 (310.40) feet to the place of beginning.

Containing 4.243 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated July 24, 1992, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin
Gordon L. Geeslin
Registered Surveyor 5372



810 EAST MARKET STREET

CELINA, OHIO 45822

J-476