

Commencing at an iron pin found at the intersection of the West right-of-way line of Walnut Street and the South side of a 16 foot alley, said iron pin being 16 feet South of the North line of Out Lot No. 4;

thence S.00°30'17"W. along the West right-of-way line of Walnut Street, a distance of 89.96 feet to a point which is the PLACE OF BEGINNING for the tract of land herein described;

thence continuing \$.00°30'17"W. along the above described line, a distance of 10.00 feet to a point;

thence N:89°26'33"W. a distance of 168.25 feet to a point;

thence N.00°33'13"W. a distance of 39.16 feet to a point;

thence N.89°39'10"E. along an existing property line, a distance of 10.00 feet to a point; thence S.00°33'13"E. a distance of 29.32 feet to a point;

thence S.89°26'33"E. a distance of 158.43 feet to the point which was the true PLACE OF BEGINNING.

Containing in all 0.045 acre being subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed references: Volume O.R. 213, pages 915-917. This plat is recorded in Survey Book "K", page 50, in the Auglaize County Engineer's Office.



ATTEST:

John W. Jauert

Professional Surveyor No. 6920

The second	
e aneri	
ASSOCIATES	
Dameston Service Control of the Cont	SHIVEVILLS AND LAND CONSULTING
RT.3 BOX 449	WAPAKONETA, OHIO 45895
PH	.(419) 738-8962 K-50

Client Dawe KELCIS
County <u>AUGLAIZE</u> Township <u>GERMAN</u>
A company
Section 10 I. 7 S., R. A. E. Drwg. No. 4-952
A for the first the second of
Drawn By J. SOUERT Date NOO. 1994
of 12 anny man 1
Scale 1"= 30 Sheet 1 of 1