

The following described tract of land is part of the Southwest Quarter of the Southwest Quarter of Section 16, Town 6 South, Range 6 East, Pusheta Township, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is at a R.R. spike over the stone found at the Southwest corner of the Southwest Quarter of Section 16, Pusheta Township and in the centerline of Township Road 110 (Freyburg Drive);

thence N.00°05'01"W. along the West line of the Southwest Quarter of Section 16, a distance of 1,330.51 feet to an iron pin set;

thence N.89°37'27"E. along the 1/4 Section line, a distance of 399.80 feet to an iron pin

thence S.00°05'01"E., parallel to the West line of the Southwest Quarter of Section 16, a distance of 498.92 feet to an iron pin set;

thence S.89°37'27"W. a distance of 115.74 feet to an iron pin set;

thence S.00°05'01"E., parallel to the West line of the Southwest Quarter of Section 16, a distance of 830.97 feet to a P.K. nail set in the centerline of Township Road 110 and the South line of the Southwest Quarter of Section 16, Pusheta Township;

thence S.89°30'00"W. along the centerline of Township Road 110 and the South line of the Southwest Quarter of Section 16, a distance of 284.06 feet to the R.R. spike which was the true PLACE OF BEGINNING.

Containing in all 10.00 acre of which 0.13 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed references: Volume 188, page 493. This plat is recorded in Survey Book "K", page 63, in the Auglaize County Engineer's Office.

