

Commencing at a monument box at the Northeast corner of the Southeast Quarter of Section 6, Goshen Township and in the centerline of County Road 261 (Waynesfield Road);

thence S.00°50'57"W. along the centerline of County Road 261 and the East line of the Southeast Quarter of Section 6, a distance of 679.43 feet to a P.K. nail set, which is the PLACE

thence continuing \$.00°50'57"W. along the above described line, a distance of 210.00 feet

thence N.89°32'19"W. parallel to the centerline of Township Road 134, a distance of 232.43 feet to an iron pin set, passing thru an iron pin set for reference at 25.00 feet in the West

thence N.00°50'57"E., parallel to the centerline of County Road 261 and the East line of the Southeast Quarter of Section 6, Goshen Township, a distance of 210.00 feet to an iron pin

thence S.89°32'19"E., parallel to the centerline of Township Road 134, a distance of 232.43 feet to the P.K. nail, passing thru an iron pin set for reference at 207.43 feet in the West right-of-way line of County Road 261, said P.K. nail was the true PLACE OF BEGINNING.

Containing in all 1.12 acre of which 0.12 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any, of record or in use on said premises. Previous deed references: Volume O.R. 24, page 836. This plat is recorded in Survey Book "K', page 149, in the Auglaize County Engineer's



Professional Surveyor No. 6920

AND LAND CONSULTING RT.3 BOX 449 WAPAKONETA, OHIO 45895

Client BEERS SURVEY County DUGLATEE Township GOSWEN SAUGUT Date OCT Sheet \_\_\_\_\_\_