

The following described tract of land is part of the Southwest Quarter of Section 5, Town 6 South, Range 8 East, Goshen Township, Auglaize County, Ohio and is more particularly described as follows:

Commencing at a monument box at the Southeast corner of the Southwest Quarter of Section 5, Goshen Township and in the centerline of Township Road 130 (Goshen Road);

thence N.89°50'00"W. along the centerline of Township Road 130 and the South line of the Southwest Quarter of Section 5, a distance of 1,121.56 feet to a P.K. Nail set and the PLACE OF BEGINNING for the tract of land herein described;

thence continuing N.89°50'00"W. along the above described line, a distance of 208.72 feet to a P.K. Nail set;

thence N.00°56'00"E. a distance of 223.72 feet to an iron pin set, passing thru an iron pin set for reference at 15.00 feet;

thence S.89°56'00"E., parallel to the centerline of Township Road 130 and the South line of the Southwest Quarter of Section 5, Goshen Township, a distance of 208.72 feet to an iron pin set;

thence S.00°56'00"W. a distance of 223.72 feet to a P.K. Nail, passing thru an iron pin set for reference at 208.72 feet, said P.K. Nail was the true PLACE OF BEGINNING.

Containing in all 1.07 Acre of which 0.07 Acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions, and reservations, if any, of record or in use on said premises. Previous deed reference: Volume O.R. 114, page 885. This plat is recorded in Survey Book "K", page 216, in the Auglaize County Engineer's Office



John W. Jauert

Professional Surveyor No. 6920



County ALCOLAIZE Township GOSAEN

Section T. G.S., R. B.E. Drwg. No. 133

Drawn By J. SAUESTDate G-Z-96

Scale A'= 100 Sheet A of A