


LOCATION PLAN



Scale:
1" = 60'

SECTION 34

E MINSTER - FT. RECOVERY RD. ↘

N.W. COR
SEC. 34
S.W. LINE, NW 1/4 SEC. 34

CHARLIE STEINEMANN
O.R. Vol. 176 Pg. 649-655

S 89°-55'-20" E
200.0'

S 89°-55'-20" E
35.0'

N 0°-44'-00" E
375.0'

CHARLIE STEINEMANN
Vol. I Pg. 776

N 0°-44'-00" E
375.0'

S 0°-44'-00" W
375.0'

LEGEND

- 'A' - MON. BOX FND.
- 'B' - R.R. SPIKE FND.
- 'C' - R.R. SPIKE SET
- 'D' - IRON PIN FND.
- 'E' - IRON PIN SET

R/W ↘
25'

S.W. CORNER
N.W. 1/4 SEC. 34

E MINSTER RD. ↘

S 89°-55'-20" E 200.0'
E MINSTER - EGYPT RD. ↗

R/W ↘

N 89°-55'-20" W
35.0'

S.E. CORNER
W 1/2, N.W. 1/4
SEC. 34

REFERENCE TO A SURVEY BY
J. FREDERICK 11-12-87

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations.
Signed: _____ Date _____

Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat.
Signed: _____ Date _____

Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed: _____
for political S.D. of: _____ Date _____

Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements.
Signed: _____ Date _____

SURVEYED BY:
Daniel J. Weaver #7472

Client CHARLIE STEINEMANN
County AUGLAIZE Twp. JACKSON Sec. 34
Drawn by _____ Scale 1" = 60' Drwg. No. _____
Checked by _____ Date _____
Sheet _____ of _____ K-280 (T 7 S; R 4 E)

Charlie Steinemann Survey

Located in the Northwest Quarter of Section 34, Town 7S, Range 4E, Jackson Township, Auglaize County, State of Ohio and being a tract of land described as follows;

Beginning at a Monument Box at the Southwest corner of the Northwest Quarter of Section 34 also being at the centerline intersection of Eiting Road and Minster-Egypt Road. Thence with the centerline of said Minster-Egypt Road South $89^{\circ}55'20''$ East for 200.0 feet to a R.R. spike and being the TRUE POINT OF BEGINNING;

Thence North $0^{\circ}44'00''$ East for 375.0 feet to an iron pin;

Thence South $89^{\circ}55'20''$ East for 35.0 feet to an iron pin;

Thence South $0^{\circ}44'00''$ West for 375.0 feet to R.R. spike in the centerline of said Minster-Egypt Road;

Thence with the centerline of Minster-Egypt Road North $89^{\circ}55'20''$ West for 35.0 feet to the point of beginning containing 0.30 acres more or less. Subject to all easements and right-of-ways of record.

This lot is not intended to be sold separately but is to become part of another lot as recorded in Vol. I Page 776.

Surveyed by

Daniel J. Weaver
Daniel J. Weaver #7472

K-281