



LOCATION PLAN

Section 18



German Township
T-7-S, R-4-E, Auglaize,
County, Ohio.

GRIESHOP SURVEY



Part of the Northeast Quarter of
Section 18, T-7-S, R-4 E,
German Township, Auglaize
County, Ohio.

State Route 274
S.89°04'54"E.

LEGEND

- Iron Pin Set
- ∅ P.K. Nail Set
- P.K. Nail Found
- Monument Box
- ▲ R.R. Spike Found

S.89°07'36"E.
1,337.30'

40.000 ACRES

0.598 Ac. R/W

Southwest corner of the
Northeast Quarter of
Section 18, German Twp.
Place of Beginning

1,338.58'
N.89°07'36"W.

C.R. 50 (Amsterdam Road)

S.00°44'16"W.

1,302.30'
S.00°44'16"W.

State Route 364
S.00°40'53"W.

This Plat is recorded in Survey Book
"K", page 660 in the Auglaize County
Engineer's Office.

ATTEST:

John W. Jauert
Professional Surveyor 6920

**Jauert
surveying**

11584 Monroe Road
Wapakoneta, Ohio
45895
(419) 657-6999

CLIENT: Grieshop Survey		
COUNTY: Auglaize	TOWNSHIP: German	SEC. 18
DRAWN BY: J.W.J.	SCALE: 1"=200'	DWG. 98-1382
CHECKED BY:	DATE: January, 1998	
SHEET 1 OF 2		(T-7-S; R-4-E)

K-660

SURVEYOR'S DESCRIPTION

The following described tract of land is part of the Southwest Quarter of the Northeast Quarter of Section 18, Town 7 South, Range 4 East, German Township, Auglaize County, Ohio and is more particularly described as follows:

The PLACE OF BEGINNING is at a monument box at the Southwest corner of the Northeast Quarter of Section 18, German Township and in the centerline of Township Road 15, (Wilker Road);

thence N.00°47'38"E. along the centerline of Township Road 15 and the West line of the Northeast Quarter of Section 18, a distance of 1,302.30 feet to a P.K. Nail set;

thence S.89°07'36"E. a distance of 1,337.30 feet to an iron pin set, passing thru an iron pin set for reference at 20.00 feet in the Easterly right-of-way line of Township Road 15;

thence S.00°44'16"W. a distance of 1,302.30 feet to an iron pin set;

thence N.89°07'36"W. along the South line of the Northeast Quarter of Section 18, a distance of 1,338.58 feet to the monument box, passing thru an iron pin set for reference at 1,318.58 feet in the Easterly right-of-way line of Township Road 15, said monument box was the true PLACE OF BEGINNING.

Containing in all 40.000 acres of which 0.598 acre has been dedicated for highway purposes. The above described tract of land is subject to all legal easements, restrictions and reservations, if any of record or in use on said premises. Previous deed reference: Volume 313, page 450. This plat is recorded in Survey Book "K", page 660, in the Auglaize County Engineer's Office. Basis of bearings is per Auglaize County Global Positioning Survey.

ATTEST:


John W. Jauert

Professional Surveyor No. 6920



Jauert
surveying

11584 Monroe Road
Wapakoneta, Ohio
45895
(419) 657-6999

CLIENT: Grieshop Survey

COUNTY: Auglaize TOWNSHIP: German SEC. 18

DRAWN BY: J.W.J. SCALE: 1"=200' DWG. 98-1382

CHECKED BY: DATE: January, 1998

SHEET 2 OF 2

(T-7-S; R-4-E)

K-661