5367+36.45 [87.5]		:\ & ct	
S89°08'07"E	, 972.81' Prisi	31\ 50\ 5129.08	
N. Line SEY	Som 22 (11)		-(2)-
64%	carrad reports of 30	Sammer Ministry	Scale: /* = 300 /
	4		<u>/* = 300 '</u>
Mido		RICHARD D	(c) ga an an an an an an an an an an an an an
l ox	\	MORRISEY 17	701 Per
6.10	\		1
Monu.fol 2 5376+19.27			3/
		\$	The second secon
	7000	of state of the st	
<u> </u>	703 Acres		
5379, 23.45 87' SN 08° 23' 49" W,	1	177 (c) st	L'E's Inc.
Monufol. 88.5		vey whi	ped:
Monu fd. 88.5 5381+03.1 88.5 SN18°02'29"W,	10'	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	up stamp up stamp d D. M
		map as a second	mark cap stamped: Richard D. Morrisey, L.S. 63 KUCK and MORRUSEY, Inc.
5383+36-25 100.5) SN 20° 50' 55'	18.05	anyting (S)	S Perm
\ '		P to volve of the position of the properties of the properties of the position	Date: 2999 Richard D. Morrisey, L.S. 670 RUCK and MORRISEY, S. 6470 Richard D. Morrisey, L.S. 6470 KUCK and MORRISEY, Inc.
5385 +67 - 34 Capped 51	s"retor	certify the accomp	in with a particle of the second of the seco
300 +67 - 3 Set (t)		y cert	topped & MC
\-\ \ \ \ 3'	36 14" W, 67.	~ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	for are topped will KUCK & MORR Date: 2/9/9
County Lord Children		7 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0 20
2/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1	10.10		Corner
	10/2 // //	Q / / 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	โมร 🖁
	25' 36"W, 40.10'		GINNING Eox @ St
5393+24-65	487.00'	F 8-30	
	N89°15'31"W, 515.19	, -	E OF BE
Josh Sta 539	370.13		0 3
70° 6' 2		513. 73. 73. 73. 73. 73. 73. 73. 73. 73. 7	BO # 50 F & F & F & F & F & F & F & F & F & F
Q'O'C IPfd @	Conal	. 60% of H	99 July 20
Sta 539	8+58.85	7	Tros
S. Line SE14 Soc.	33	N 89° /2'27' 434	W, 10
	· ·	1189°12'27"	W, 76.72
		TRES fd 6283°25'22	#E, 0.57
Signature by a representative of the County I denotes compliance with Health Regulations.	Planning Co	by a representative of the Auglaize Cour commission denotes approval of this plat	nty Regional
Signed: Dat	eSigned:	Date	e
Signature by a representative of City with 3 mi	e limit iuric		
diction or Twp. Trustees or Village with goning	jurisdiction Signature b denotes tha	by a representative of the County Engi it this plat meets tax map plat requireme	ente
denotes approval of this plat. Signed: for political S. D. of: Dat	eSigned:	Date	
KUCK and MORRISEY, INC.	Client Joe MAC		3)
CONSULTING ENGINEERS & SURVEYORS LIMA, OHIO 45805	County Auglaize Drawn by RDM	Scale Drwg No.	
TELEPHONE 228-1735 - AREA CODE 419 2807 CHAPEL HILL DRIVE	Checked by	Date	3
		(T-4-S;	R <u>-4-</u> E)

L-256

3. 50

Towns and the second

DESCRIPTION

Being a part of the Southeast quarter of Section 23, T-4-S, R-4-E, Salem Township, Auglaize County, Ohio and more particularly described as follows:

Scale:

Commencing at an iron pin found in a monument box at the southeast corner of said Southeast quarter of said Section 23; thence N 89°12'27" W (basis of bearing - calculated) with the south line of said Southeast quarter (also the centerline of I.O.O.F. Rd.), 76.72 feet to a PK nail and shinner set at the intersection of said south line and centerline with the centerline of State Route 66 (Station 1154+08.06 on said centerline of State Route 66) and the PLACE OF BEGINNING thence continuing N 89°12'27" W with said south line and centerline, 484.84 feet to a point on the east line of a 5.00 acres survey (see Survey Book G Page 626) (Railroad spike from previous survey found S 28°23'24" E, 0.57 feet); thence N 28^o23'24" W (passing through a capped rebar found at 24.46 feet), 513.73 feet to a rebar found badly bent and replaced with a capped 58 inch rebar; thence N 89015'31" W (passing through a capped 5/8 inch rebar found at 487.00 feet), 515.19 feet to a capped 5/8 inch rebar set on the east state property line for the Miami & Erie Canal; thence northwesterly the following seven courses that define the meanderings of said east state property line: N 31°25'36" W, 70.10 feet to a capped 5/8 inch rebar set; N 31°36'14" W, 752.67 feet to a capped 5/8 inch rebar set; thence N 20°30'55" W, 218.05 feet to a capped 5/8 inch rebar set; N 18^o02'29" W, 219.40 feet to a capped 5/8 inch rebar set; thence N 08^o23'49" W, 164.65 feet to a capped 5/8 inch rebar set; thence N 01^o46'33" W, 304.01 feet to a capped 5/8 inch rebar set; thence N 01°42'39" W, 642.97 feet to a capped 5/8 inch rebar set on the north line of said Southeast quarter; thence S 89008'07" E with said north line (passing through a capped 5/8 inch rebar set at 914.48 feet), 972.81 feet to a PK nail and shinner set on the centerline of State Route 66 (being Station 1182+29.08); thence S 18^o35'39" E with said centerline of said State Route 66 (passing through a PK nail set at Station 1168+00.00), 2,821.02 feet to the PLACE OF BEGINNING containing 65.703 acres more or less and subject to all highway and other legal easements of record. Road right-of-way occupies 3.930 acres. Being part of Parcel J 27-023-009-00 Deed Reference: Volume O.R. 265, Page 760

I hereby certify the accompanying map and survey which it represents to be correct to the best of my knowledge and belief. All rebar set and called for are topped with a plastic Peramark cap stamped: KUCK & MORRISEY L.S. 6470

Date: 2/9/98

Richard D. Morrisey, L.S. 6470 Kuck and Morrisey, Inc.

State OF Orthon	
RICHARD D. A B	
8470 S	
SURVE	

Signature by a representative of the County Health Dept. denotes compliance with Health Regulations. Signed: Date		Signature by a representative of the Auglaize County Regional Planning Commission denotes approval of this plat. Signed: Date	
Signature by a representative of City with 3 mile limit jurisdiction or Twp. Trustees or Village with zoning jurisdiction denotes approval of this plat. Signed:		Signature by a representative of the County Engineer's Dept. denotes that this plat meets tax map plat requirements. Signed: Date	
KUCK and MORRISEY, INC. CONSULTING ENGINEERS & SURVEYORS LIMA, OHIO 45805 TELEPHONE 228-1735 - AREA CODE 419 2807 CHAPEL HILL DRIVE	County 🔑 Drawn by Checked by	OF MACK Twp. SALEM Sec. 200 From Scale Drwg. No. Date 2000	