


W. LINE - SEC. 28 & LAMBERT RD.

S. 00° 23' 59" W.
270.70

LEGEND

- "A" = IRON BAR IN MON. BOX @ W. 1/4 POST ~ SEC. 28.
- "B" = MINE SPIKE FD.
- "C" = R.R. SPIKE FD @ E STA. 56 + 82.53 (S.H. 482 R/W PLANS).
- "D" = MINE SPIKE SET.
- "E" = 5/8" x 30" IRON BAR SET.

LOCATION SKETCH



SECTION 28

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN, P.S. 5372

5.001 ACRES

N. 89° 55' 31" E. ~ 2138.64
N. 89° 55' 31" E. ~ 973.05
S. 89° 55' 31" W. ~ 1052.33
N. 00° 04' 29" W. ~ 215.11

KENNETH & MALINDA DANMEYER
O.R. VOL. 67, PG. 915

SCHULTZ SURVEY

PART OF THE S.W. 1/4 OF SECTION 28, T.5 S.,
R. 4 E., (NOBLE TOWNSHIP), AUGLAIZE
COUNTY, OHIO.

MARCH 31, 1993

SCALE 1" = 100'


PERMANENT
PARCEL No.

Part of: Sec. T R Township
Grantor: Area Retained: Acres
Grantee: Area Transferred: Acres
Deed References:

APPROVALS:
AGENCY: Board of Health
DATE:

County Engineer

County Sanitary Engineer



ORDON L. GEESLIN

LAND SURVEYOR

810 EAST MARKET STREET

CELINA, OHIO

PHONE (419) 586-6155

L-516

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

March 31, 1993

SCHULTZ SURVEY DESCRIPTION

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the southwest quarter of Section 28, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at an iron bar in an Auglaize County Monument Box Assembly at the northwest corner of the southwest quarter of said Section 28-

Thence, south $00^{\circ}23'59''$ west, along the west line of the southwest quarter of said Section 28 and the centerline of Lambert Road, a distance of two hundred seventy and $70/100$ (270.70) feet to a mine spike-

Thence, north $89^{\circ}55'31''$ east, a distance of two thousand one hundred thirty-eight and $64/100$ (2138.64) feet to a mine spike in the centerline of State Route 116-

Thence, south $20^{\circ}18'18''$ east, along the centerline of State Route 116, a distance of two hundred seventy-seven and $14/100$ (277.14) feet to a mine spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing, south $20^{\circ}18'18''$ east, along the last described line, a distance of two hundred twenty-nine and $26/100$ (229.26) feet to a mine spike-

Thence, south $89^{\circ}55'31''$ west, a distance of one thousand fifty-two and $33/100$ (1052.33) feet to a $5/8$ inch iron bar-

Thence, north $00^{\circ}04'29''$ west, a distance of two hundred fifteen and $11/100$ (215.11) feet to a $5/8$ inch iron bar-

Thence, north $89^{\circ}55'31''$ east, a distance of nine hundred seventy-three and $05/100$ (973.05) feet to the place of beginning.

Containing 5.001 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated March 31, 1993, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin
Registered Surveyor 5372