



PART OF THE SW 1/4
OF SECTION 20, T-7-S, R-4-E,
JACKSON TWP, AUGLAIZE CO.,
OHIO



scale: 1" = 100'

2001.66'
to Stone @ Center


N. LINE; SW 1/4; SEC. 20

N 89° 52' 04" E

330'

667.22'

337.22'



HARRY HEITKAMP
VOL 257, PG 72
5.0 AC.

12.078 ACRES O.A.

0.535 AC. R/W

7.078 AC.

Q & SR 364; W. LINE; SW 1/4; SEC. 20

N 00° 10' 35" E

788.17'

660'

660'

N 00° 10' 35" E

788.36'

S 0° 08' 26" W

30'

N 89° 52' 04" E

330'

667.71'

S 89° 53' 04" W

SR 119

SW COR, SEC 20

James M. Kent, P.S. 6792 OH

JAMES M.
KENT
6792

LEGEND

⊗ PK NAIL (FD)

⊙ GIN SPINDLE (SET)

○ 5/8" RE-ROD W/CAP (SET)

BASIS OF BEARINGS

REF - SURVEY BY J. JAUERT I-342

CLIENT H. HEITKAMP DATE 6/28/96
COUNTY AUGLAIZE TOWNSHIP JACKSON
SECTION 20 T-7-S; R-4-E
DRAWN BY JMK DRAWING NO. 2491
SHEET 1 OF 2

L-583

kent
surveying

p.o. box 96 • 419/738-5677
wapakoneta, ohio