

the Southeast Quarter of Section 5, a distance of 201.68 feet to a Mag Nail set, which

thence continuing S.02°09'00"W. along the above described line, a distance of 245.08 feet to a Mag Nail reset in the intersection of the centerlines of County Road 91 and State Route 197;

thence N.76°08'00"W. along the centerline of State Route 197, a distance of 673.31 feet to a P.K. Nail found;

thence N.05°48'18"E. a distance of 101.34 feet to a point in the centerline of

a County Permanent Maintenance Open Ditch;

thence N.15°40'09"W. along the centerline of said County Permanent Maintenance Ditch, a distance of 211.14 feet to a point; thence S.87°33'25"E. a distance of 426.81 feet to an iron pin set, passing thru

an iron pin set for reference at 20.00 feet on the top of the open ditch bank; thence S.01°52'40"W. a distance of 198.58 feet to an iron pin set;

thence S.89°13'39"E. a distance of 289.39 feet to a Mag Nail set, passing thru an iron pin set for reference at 264.76 feet in the West right-of-way line of C.R. 91, said Mag Nail was the true PLACE OF BEGINNING;

Containing in all 4.395 acres of which 0.587 acre has been dedicated for highway purposes. The above described tract of land is subject to all restrictions, easements and reservations, if any, of record or in use on said premises. Previous This plat is recorded in Survey Book "M",

Deed reference: Volume O.R. 291, page 333. This page 400, in the Anglaize County Engineer's Office. Basis of bearings is from a previous survey, see Survey Book "K", Page 236.

ATTEST:

Jauert Professional Surveyor No. 6920 surveying

Wapakoneta, Ohio 45895

CLIENT: Jeff Hager	
COUNTY: Auglaize	TOWNSHIP: Logan SEC. 5
DRAWN BY: J.W.J.	SCALE: 1'=150' DWG.# 01-2245
CHECKED BY:	DATE: September, 2001 2255
SHEET 1 OF 1	(T-5-S; R-5-E)