

H. LINE ~ N.W. 1/4 ~ SEC. 1 & GEIGE RD "B"

EAST ~ 592.01'

EAST ~ 2070.3

LEGEND

"A" = COR. STONE AT
N.W. COR. SEC. 1.


"B" = IRON PIPE AT
N. 1/4 POST ~ SEC. 1.

"C" = P.K. NAIL IN E
COUNTY ROAD 33-A


"D" = 5/8" IRON BAR
FD. FROM SURVEY
BY M. WEADOCK
DATED 5-5-1980.

"E" = 5/8" X 30" IRON BAR
SET.

LOCATION SKETCH



SECTION 1



N. 89° 35' 22" W.

340.50

5.186
ACRES

S. 00° 24' 38" W.
452.44

N. 00° 24' 38" E.
502.44

N. 89° 35' 22" W.
199.15'

S. 89° 35' 22" E. - 489.49

S. 00° 14' 12" W.
273.03

N. 00° 14' 12" E.
372.49

"E"
S. 89° 41' 30" W.
175.00

"E"
S. 00° 14' 12" W.
150.00

N. 89° 41' 30" E.
225.00

N. 00° 14' 12" E.
458.04

WILKER SURVEY

PART OF THE W. 1/2 OF THE
N.W. 1/4 OF SECTION 1, TOWN
6 SOUTH, RANGE 4 EAST
(ST. MARYS TWP.), AUGLAIZE
COUNTY, OHIO.

E. COUNTY ROAD 33-A

FEB. 14, 1990 SCALE 1"=200'

SURVEYED BY Gordon L. Geeslin
GORDON L. GEESLIN
REGISTERED SURVEYOR
N# 5372

GORDON L. GEESLIN

LAND SURVEYOR

810 EAST MARKET STREET

CELINA, OHIO

PHONE (419) 586-6155



PERMANENT
PARCEL No. _____

Part of: _____ Sec. _____ T _____ R _____ Township

Grantor: _____ Area Retained: _____ Acres

Grantee: _____ Area Transferred: _____ Acres

Deed References: _____

APPROVALS
AGENCY
DATE

Board of Health

County Sanitary Engineer

County Engineer

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

February 14, 1990

WILKER SURVEY DESCRIPTION

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the west half of the northwest quarter of Section 1, Township 6 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at the corner stone at the northwest corner of said Section 1-

Thence, east, along the north line of the northwest quarter of said Section 1 and the centerline of Geiger Road, a distance of five hundred ninety-two and 01/100 (592.01) feet to a point-

Thence, south 00°24'38" west, a distance of seven hundred forty-two and 20/100 (742.20) feet to a point. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing south 00°24'38" west, a distance of four hundred fifty-two and 44/100 (452.44) feet to a point-

Thence, north 89°35'22" west, a distance of one hundred ninety-nine and 15/100 (199.15) feet to a point-

Thence, south 00°14'12" west, a distance of two hundred seventy-three and 03/100 (273.03) feet to a 5/8 inch iron bar-

Thence, south 89°47'30" west, a distance of one hundred seventy-five (175.00) feet to a 5/8 inch iron bar-

Thence, south 00°14'12" west, a distance of one hundred fifty (150.00) feet to a 5/8 inch iron bar in the north line of a 2.192 acre tract of land conveyed to Dennis Peterson by deed recorded in O.R. Volume 64, page 486-

Thence north 89°47'30" east, along said Peterson's north line and the north line of a 2.808 acre tract of land conveyed to John Tompary by deed recored in O. R. Volume 92, page 86, a distance of two hundred twenty-five (225.00) feet to a 5/8 inch iron bar at the northeast corner of said Tompary's tract of land-

Thence, north 00°14'12" east, a distance of three hundred seventy-two and 49/100 (372.49) feet to a point-

Thence, south 89°35'22" east, a distance of four hundred eighty-nine and 49/100 (489.49) feet to a point-

Thence, north 00°24'38" east, a distance of five hundred two and 44/100 (502.44) feet to a point-

Continued page 2.

Account 123

2.

WILKER SURVEY DESCRIPTION CONTINUED:

Thence, north 89°35'22" west, a distance of three hundred forty and 50/100 (340.50) feet to the place of beginning.

Containing 5.186 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Registered Surveyor 5372, dated February 14, 1990, on file in the County Engineer's Office.

Surveyed by

Gordon L. Geeslin

Gordon L. Geeslin

Registered Surveyor 5372

