


PART ~ N. E.  $\frac{1}{4}$  ~ S. E.  $\frac{1}{4}$  ~ SEC 28, (ST. MARYS  
TOWNSHIP), T. 6 S., R. 4 E., AUGLAIZE  
COUNTY, OHIO.

SCALE 1" = 200'



### LEGEND

"B" = R.R. SPIKE FD.

\*C\* = 1" IRON BAR FD.

\*D\* = P.K. NAIL SET

E = 5/8" IRON BAR  
SET @ 30.00.


"F" = 5/8" IRON BAR SET.

"G" = 5/8" IRON BAR SET @  
PRIOR LOCATION OF  
A STEEL COR. POST.

**GEESLIN  
LAND SURVEYING**

810 EAST MARKET STREET  
CELINA, OHIO

PHONE (419) 536-6155



---

PERMANENT  
PARCEL No. \_\_\_\_\_

Part of: \_\_\_\_\_ Sec. \_\_\_\_\_ T. \_\_\_\_\_ R. \_\_\_\_\_ Township \_\_\_\_\_

Grantor: \_\_\_\_\_ Area Retained: \_\_\_\_\_ Acres \_\_\_\_\_

Grantee: \_\_\_\_\_ Area Transferred: \_\_\_\_\_ Acres \_\_\_\_\_

Deed References: \_\_\_\_\_

---

APPROVALS  
AGENCY \_\_\_\_\_

Board of Health \_\_\_\_\_ County Sealer/Engineer \_\_\_\_\_ County Engineer \_\_\_\_\_

VI-206

Aug. Co. Eng.

**GORDON L. GEESLIN**

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

May 9, 1995

VONDENHUEVEL SURVEY DESCRIPTION

Being a parcel of land situated in St. Marys Township, Auglaize County, Ohio, in the northeast quarter of the southeast quarter of Section 28, Township 6 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at an iron bar in an Auglaize County Monument Box Assembly. Said point being at the intersection of the East-West half section line and the centerline of County Road 66-A-

Thence, south  $5^{\circ}37'10''$  west, along the centerline of said County Road 66-A, a distance of four hundred fifteen and  $30/100$  (415.30) feet to a "P.K." nail. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing, south  $5^{\circ}37'10''$  west, along the last described line, a distance of forty and  $79/100$  (40.79) feet to a "P.K." nail-

Thence, north  $89^{\circ}49'50''$  west, a distance of one thousand seventy and  $91/100$  (1070.91) feet to a  $5/8$  inch iron bar-

Thence, north  $0^{\circ}19'40''$  east, a distance of forty and  $61/100$  (40.61) feet to a  $5/8$  inch iron bar-

Thence, south  $89^{\circ}49'50''$  east, a distance of one thousand seventy-four and  $67/100$  (1074.67) feet to the place of beginning.

Containing 1.000 acre of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Professional Surveyor 5372, dated May 9, 1995, on file in the County Engineer's Office.

Surveyed by Gordon L. Geeslin  
Gordon L. Geeslin  
Professional Surveyor 5372

