

[illegible]

SURVEYED BY Gordon L. Geslin
GORDON L. GEESLIN
FS 5372

A hand-drawn sketch map of the Hussey Creek area. A diagonal line represents Hussey Creek, with the words "HUSSEY CREEK" written along it. A horizontal line represents a road. A vertical line connects the road to the creek. To the right of the road, there is a small rectangle representing a building, with the letters "L S 9" written next to it.

LINE FROM PRIOR
SURVEY FOR HOTTLE,
9/80.

N. 89° 48' 00" E.

TRACT A-2
1.377 ACRES

5.89° 48' 00" W.

TRACT A-1

1.377 ACRES

TRACT B²)

2.755 ACRES

א
ז
ש
ט
י
כ

1. 4
 2. 4
 3. 4
 4. 4
 5. 4
 6. 4
 7. 4
 8. 4
 9. 4
 10. 4
 11. 4
 12. 4
 13. 4
 14. 4
 15. 4
 16. 4
 17. 4
 18. 4
 19. 4
 20. 4
 21. 4
 22. 4
 23. 4
 24. 4
 25. 4
 26. 4
 27. 4
 28. 4
 29. 4
 30. 4
 31. 4
 32. 4
 33. 4
 34. 4
 35. 4
 36. 4
 37. 4
 38. 4
 39. 4
 40. 4
 41. 4
 42. 4
 43. 4
 44. 4
 45. 4
 46. 4
 47. 4
 48. 4
 49. 4
 50. 4
 51. 4
 52. 4
 53. 4
 54. 4
 55. 4
 56. 4
 57. 4
 58. 4
 59. 4
 60. 4
 61. 4
 62. 4
 63. 4
 64. 4
 65. 4
 66. 4
 67. 4
 68. 4
 69. 4
 70. 4
 71. 4
 72. 4
 73. 4
 74. 4
 75. 4
 76. 4
 77. 4
 78. 4
 79. 4
 80. 4
 81. 4
 82. 4
 83. 4
 84. 4
 85. 4
 86. 4
 87. 4
 88. 4
 89. 4
 90. 4
 91. 4
 92. 4
 93. 4
 94. 4
 95. 4
 96. 4
 97. 4
 98. 4
 99. 4
 100. 4

043533110

2003.07.24

THESE
||
D

"E" = 5/8" x 30" IRON BAR SET ON 3 LINE

"F" = 5/8" x 30' IRON BAR SET @ 18" 45' FROM E.

5/50 x 30' BOZ BAR SET.

ROCKWOOD
O.R.VOL. 2, PG. 120

S. 1/4 PLOT
SEC 18

25 A

15

O' RIGHT

5

OF-WAY LINE

10

S.E. COR
S.E. COR

S. LINE ~ S.E. 1/4 ~ SEC. 18 & E NOBLE RD.

PART OF THE E. $\frac{1}{2}$ OF THE S. E. $\frac{1}{4}$ OF SECTION
18, T. 5 S., R. 4 E., (NOBLE TOWNSHIP),
AUGLAIZE COUNTY, OHIO.

NOVEMBER 1, 1993

SCALE 1" = 100'




N-832

REVISED 2 JUNE 1995

GORDON L. GEESLIN

LAND SURVEYOR

810 EAST MARKET STREET



PERMANENT
PARCEL No.

Part of: _____ Sec. 18 T 55 R 4E North Township

Grantor: _____ Area Retained: _____ Acres

Grantee: _____ Area Transferred: _____ Acres

GORDON L. GEESLIN

REGISTERED LAND SURVEYOR

PHONE 419-586-6155

June 2, 1995

ELSTON SURVEY DESCRIPTION (TRACT A-1)

Being a parcel of land situated in Noble Township, Auglaize County, Ohio, in the east half of the southeast quarter of Section 18, Township 5 South, Range 4 East. Being more particularly described as follows:

Commencing for reference at the cornerstone at the southeast corner of said Section 18-

Thence, south $89^{\circ}48'$ west, along the south line of the southeast quarter of said Section 18 and the centerline of Noble Road, a distance of nine hundred thirty-one and $37/100$ (931.37) feet to a mine spike. Said point being the place of beginning for the parcel to be conveyed by this instrument-

Thence, continuing, south $89^{\circ}48'$ west, along the last described line, a distance of two hundred (200.00) feet to a mine spike-

Thence, north $00^{\circ}00'55''$ east, a distance of three hundred (300.00) feet to a point-

Thence, north $89^{\circ}48'$ east, a distance of two hundred (200.00) feet to a $5/8$ inch iron bar-

Thence, south $00^{\circ}00'55''$ west, a distance of three hundred (300.00) feet to the place of beginning.

Containing 1.377 acres of land more or less.

Subject to all easements and right-of-way of record.

Reference is made to a survey of this area by Gordon L. Geeslin, Professional Surveyor 5372, dated November 1, 1993, on file in the County Engineer's Office.

Surveyed by *Gordon L. Geeslin*
Gordon L. Geeslin
Professional Surveyor 5372

