

Thomas W. Steinke Professional Registered Surveyor #6177 Land Surveying

16454 County Road # 25-A

Anna, Ohio 45302 E-mail: tssurvey@bright.net

Phone: (937) 693-6538



Date: June 21, 2004

Description of 6.637 Acres for F. Brown

Being 6.637 Acres located in the northeast quarter of Section 19, Town 6 South, Range 6 East, Pusheta Township, Auglaize County, Ohio and being further described as follows:

Commencing at a railroad spike located at the Centerline intersection of Hardin~Wapak Road and Headapohl Road (See Survey Book "G", Page 515).

Thence South 88 41' 10" West along the centerline of Headapohl Road, a distance of 1416.84 feet to a PK Spike set and PLACE OF BEGINNING for the parcel herein described.

Thence continuing South 88° 41′ 10″ West along said centerline, a distance of 20.00 feet to a monument box located in the west line of the northeast quarter of Section 19;

Thence North 00° 51′ 50″ West along the west line of the north east quarter of Section 19, a distance of 875.15 feet to an iron bar set, passing through an iron bar found at 16.5 feet;

Thence continuing North 00° 51′ 50″ West, a distance of 879.34 feet to a corner stone at the northwest corner of the northeast quarter of Section 19;

Thence North 89° 00′ 50″ East along the north line of Section 19, a distance of 303.65 feet to an iron bar set;

Thence South 01° 27' 33" East, a distance of 882.97 feet to an iron bar set;

Thence South 89° 40′ 23" West, a distance of 292.83 feet to an iron bar set;

Thence South 00° 51′ 50″ East parallel to the quarter section line, a distance of 874.81 feet to the PLACE OF BEGINNING, passing through an iron bar set at 858.31 feet.

Containing in all 6.637 Acres of which 0.008 acre is located within the existing road right of way. Survey & description prepared by Thomas W. Steinke, Registered Surveyor # 6177, on this 21^{st} day of June, 2004 and based upon existing records. Basis of bearings, see Survey Book "G", Page 515