

**Legal Description for Deed
Dammeyer Survey
Michael Dammeyer, Grantor.**

Real Estate situated in German Township, Auglaize County, State of Ohio and bounded and described as follows:

Tract 1:

Being a tract in the Southwest Quarter of Section 3, Town 7 South, Range 4 East, commencing at a monument box at the Southeast corner of the Southwest Quarter of said Section 3; thence North $88^{\circ} 53' 30''$ West 687.20 feet along the South line of the Southwest Quarter of said Section 3 and centerline of Lock Two Road to a mag nail in the approximate center of a bridge deck over Koop Creek, for the true point of beginning;

thence continuing North $88^{\circ} 53' 30''$ West 757.77 feet along the South line of the Southwest Quarter of said Section 3 and centerline of Lock Two Road to an iron pin in a monument box;

thence North $11^{\circ} 02' 12''$ West 62.73 feet along the centerline of County Road 66A to an iron pin in a monument box;

thence North $21^{\circ} 02' 23''$ West 427.28 feet along the centerline of County Road 66A to a railroad spike;

thence South $88^{\circ} 53' 30''$ East 1121.43 feet to a point, passing through an iron pin at 400.48 feet and then passing through an iron reference pin North $88^{\circ} 53' 30''$ West 20.78 feet from said point;

thence South $16^{\circ} 51' 07''$ West 289.02 feet along the approximate centerline of Koop creek to a point, reference an iron pin North $73^{\circ} 08' 53''$ West 20.00 feet;

thence South $32^{\circ} 54' 53''$ West 210.51 feet along the approximate centerline of Koop Creek to the point of beginning containing 9.999 acres of land more or less of which 0.761 acre has been dedicated for highway purposes.

Said tract shall also be subject to highways and any other easement or restriction of record.

Basis of bearing on the south line of the Southwest Quarter of Section 3 and centerline of Lock Two Road is from Auglaize County Global Positioning System Records.

Previous Deed Reference: Official Record 219, Page 220.

Description from survey completed on March 7, 2005 by Steven H. Kremer, Registered Surveyor No. 7487.

0-793

**Legal Description for Deed
Dammeyer Survey
Michael Dammeyer, Grantor.**

Real Estate situated in German Township, Auglaize County, State of Ohio and bounded and described as follows:

Tract 2:

Being a tract in the Southwest Quarter of Section 3, Town 7 South, Range 4 East, commencing at a monument box at the Southeast corner of the Southwest Quarter of said Section 3; thence North $88^{\circ} 53' 30''$ West 1444.97 feet along the South line of the Southwest Quarter of said Section 3 and centerline of Lock Two Road to an iron pin in a monument box; thence North $11^{\circ} 02' 12''$ West 62.73 feet along the centerline of County Road 66A to an iron pin in a monument box; thence North $21^{\circ} 02' 23''$ West 427.28 feet along the centerline of County Road 66A to a railroad spike for the true point of beginning;

Thence continuing North $21^{\circ} 02' 23''$ West 479.21 feet along the centerline of County Road 66A to a railroad spike;

thence South $88^{\circ} 53' 30''$ East 581.14 feet to an iron pin;

thence South $01^{\circ} 06' 30''$ West 443.85 feet to an iron pin;

thence North $88^{\circ} 53' 30''$ West 400.48 feet to the point of beginning containing 5.001 acres of land more or less of which 0.330 acre has been dedicated for highway purposes.

Said tract shall also be subject to highways and any other easement or restriction of record.

Basis of bearing on the south line of the Southwest Quarter of Section 3 and centerline of Lock Two Road is from Auglaize County Global Positioning System Records.

Previous Deed Reference: Official Record 219, Page 220.

Description from survey completed on March 7, 2005 by Steven H. Kremer, Registered Surveyor No. 7487.

0-794

**Legal Description for Deed
Dammeyer Survey
Michael Dammeyer, Grantor.**

Real Estate situated in German Township, Auglaize County, State of Ohio and bounded and described as follows:

Tract 3:

Being a tract in the Southwest Quarter of Section 3, Town 7 South, Range 4 East, commencing at a monument box at the Southeast corner of the Southwest Quarter of said Section 3; thence North 88° 53' 30" West 1444.97 feet along the South line of the Southwest Quarter of said Section 3 and centerline of Lock Two Road to an iron pin in a monument box; thence North 11° 02' 12" West 62.73 feet along the centerline of County Road 66A to an iron pin in a monument box; thence North 21° 02' 23" West 906.49 feet along the centerline of County Road 66A to a railroad spike for the true point of beginning;

thence continuing North 21° 02' 23" West 362.17 feet along the centerline of County Road 66A to a railroad spike;

thence South 88° 53' 30" East 717.68 feet to an iron pin;

thence South 01° 06' 30" West 335.45 feet to an iron pin;

thence North 88° 53' 30" West 581.14 feet to the point of beginning containing 5.001 acres of land more or less of which 0.249 acre has been dedicated for highway purposes.

Said tract shall also be subject to highways and any other easement or restriction of record.

Basis of bearing on the south line of the Southwest Quarter of Section 3 and centerline of Lock Two Road is from Auglaize County Global Positioning System Records.

Previous Deed Reference: Official Record 219, Page 220.

Description from survey completed on March 7, 2005 by Steven H. Kremer, Registered Surveyor No. 7487.

0-795

**Legal Description for Deed
Dammeyer Survey
Michael Dammeyer, Grantor.**

Real Estate situated in German Township, Auglaize County, State of Ohio and bounded and described as follows:

Tract 4:

Being a tract in the Southwest Quarter of Section 3, Town 7 South, Range 4 East, commencing at a monument box at the Southeast corner of the Southwest Quarter of said Section 3; thence North $88^{\circ} 53' 30''$ West 1444.97 feet along the South line of the Southwest Quarter of said Section 3 and centerline of Lock Two Road to an iron pin in a monument box; thence North $11^{\circ} 02' 12''$ West 62.73 feet along the centerline of County Road 66A to an iron pin in a monument box; thence North $21^{\circ} 02' 23''$ West 1268.66 feet along the centerline of County Road 66A to a railroad spike for the true point of beginning;

thence continuing North $21^{\circ} 02' 23''$ West 303.73 feet along the centerline of County Road 66A to a railroad spike;

thence South $88^{\circ} 51' 53''$ East 832.19 feet to an iron pin;

thence South $01^{\circ} 06' 30''$ West 280.93 feet to an iron pin;

thence North $88^{\circ} 53' 30''$ West 717.68 feet to the point of beginning containing 5.001 acres of land more or less of which 0.209 acre has been dedicated for highway purposes.

Said tract shall also be subject to highways and any other easement or restriction of record.

Basis of bearing on the south line of the Southwest Quarter of Section 3 and centerline of Lock Two Road is from Auglaize County Global Positioning System Records.

Previous Deed Reference: Official Record 219, Page 220.

Description from survey completed on March 7, 2005 by Steven H. Kremer, Registered Surveyor No. 7487.

0-796