

Bacon & Associates

750 N. Eastown Road

Engineering and Surveying Phone: (419) 999-3756 FAX: (419) 999-2523

Elida, Ohio 45807

DESCRIPTION (1.769 Parcel)

Being a parcel of land in the NW¹/₄ of Section 5, T6S, R4E, St. Marys Township, Auglaize County, Ohio, more particularly described as follows:

Beginning at a set Mag nail at the P.T. on the centerline of R/W of S.R. 703 at ODOT Sta. 64+93.09, said point being N.22°-06'-17''E., 30.00' from an ODOT concrete monument, thence the following courses;

- 1. Northwesterly on the centerline of S.R. 703 on a curve to the right, 144.16' to a set Mag nail said curve having a radius of 1909.86' and a chord of N.65°-43'-59"W., 144.12';
- 2. N.24°-41'-02"E., 427.11' to a set #5 rebar on the south R/W line of the RR, passing over a set #5 rebar at 30.01';
- 3. S.60°-07'-51"E. on said south RR R/W line, 173.43' to a set #5 rebar;
- 4. S.21°-30'-52"W., 408.71' to a set Mag nail on the centerline of S.R. 703, passing over a set #5 rebar at 378.71';
- 5. N.67°-53'-43"W. on the centerline of S.R. 703, 51.25' to the POINT OF BEGINNING.

The above-described parcel contains 1.769 acres, more or less, subject to all legal highways and easements of record at the time of survey.

A bearing of N.67°-53'-43"W. was assumed for the centerline of S.R. 703 R/W between the P.T. Sta. 64+93.09 and the P.C. Sta. 70+60.51.

Prior D.V. 56, Page 165.

This plat and description is based on a field survey on 5-5-05 by, Bacon & Associates, LLC under direction of Clayton T. Bacon, P.S. #6179.

MAMMIN 0F FGISTERE SIONAL SU 3

7-61

Bacon & Associates

750 N. Eastown Road

Engineering and Surveying Phone: (419) 999-3756 FAX: (419) 999-2523

Elida, Ohio 45807

DESCRIPTION (1.455 Parcel)

Being a parcel of land in the NW¼ of Section 5, T6S, R4E, St. Marys Township, Auglaize County, Ohio, more particularly described as follows:


Commencing for reference at a set Mag nail at the P.T. on the centerline of R/W of S.R. 703 at ODOT Sta. 64+93.09, said point being N.22°-06'-17"E., 30.00' from an ODOT concrete monument, thence S.67°-53'-43"E. (assumed bearing) on the centerline of S.R. 703, 51.25' to a set Mag nail at the POINT OF BEGINNING of the parcel to be described, thence the following courses;

- 1. N.21°-30'-52"E., 408.71' to a set #5 rebar on the south RR R/W line, passing over a set #5 rebar at 30.00';
- 2. S.60°-07'-51"E. on said south line, 161.07' to a set #5 rebar;
- 3. S.21°-30'-52"W., 386.94' to a set Mag nail on the centerline of S.R. 703, passing over a set #5 rebar at 356.94';
- 4. N.67°-53'-43"W. on the centerline of S.R. 703, 159.37' to the POINT OF BEGINNING.

The above-described parcel contains 1.455 acres, more or less, subject to all legal highways and easements of record at the time of survey.

Prior D.V. 56, Page 165.

This plat and description is based on a field survey on 5-05-05 by, Bacon & Associates, LLC under direction of Clayton T. Bacon, P.S. #6179.



P-62

Bacon & Associates

750 N. Eastown Road

Engineering and Surveying Phone: (419) 999-3756 FAX: (419) 999-2523

Elida, Ohio 45807

DESCRIPTION (3.410 Parcel)

Being a parcel of land in the NW¹/₄ of Section 5, T6S, R4E, St. Marys Township, Auglaize County, Ohio, more particularly described as follows:

Commencing for reference at a set Mag nail at the P.T. on the centerline of R/W of S.R. 703 at ODOT Sta. 64+93.09. Said point being N.22°-06'-17"E., 30.00' from an ODOT concrete monument marking said point, thence S.67°-53'-43"E. on the centerline of S.R. 703, 210.62' to a set Mag nail at the POINT OF BEGINNING, thence the following courses;


- 1. N.21°-30'-52"E., 386.94' to a set #5 rebar on the south RR R/W line, passing over a set #5 rebar at 30.00';
- 2. S.60°-07'-51"E. on said south line, 419.45' to a set #5 rebar;
- 3. S.21°-53'-02"W., 329.98' to a set Mag nail on the centerline of S.R. 703, passing over a set #5 rebar at 284.49';
- 4. Northwesterly on a non-tangential curve to the right on the centerline of S.R. 703, 56.10' to a set Mag nail at the ODOT P.C. Sta. 70+60.51. said curve having a radius of 5729.58' and a chord of N.68°-10'-33"W., 56.10';
- 5. N.67°-53'-43"W. on the centerline of S.R. 703, 356.80' to the POINT OF BEGINNING.

The above-described parcel contains 3.410 acres, more or less, subject to all legal highways and easements of record at the time of survey.

A bearing of N.67°-53'-43"W. was assumed for the centerline of S.R. 703 R/W between the P.T. Sta. 64+93.09 and the P.C. Sta. 70+60.51.

Prior D.V. 56, Page 165

This plat and description is based on a field survey on 5-05-05 by, Bacon & Associates, LLC under direction of Clayton T. Bacon, P.S. #6179.



P-63