SOMMER FARMS, LLC SURVEY

5.010 Acres being a part of the West Half of the Southeast Quarter of Section 29, Jackson Township, Town-7-South, Range-4-East,



County of Auglaize, State of Ohio

PREVIOUS DEED REFERENCES


Volume OR 534 Page <u>1783</u>

This Survey Plat and Description is Recorded in Survey Book $_$, Page $\underline{279}$, Auglaize County Engineer's Tax Map Office.

NOTE

The Basis of Bearings used for this Survey was determined from the Auglaize County Engineer's Global Positioning Survey






Section 29, Jackson Twp. Auglaize County, Ohio

ATTEST

Ted K. Schnell Professional Engineer Professional Surveyor



JACKSON

H & S Civil Engineers and Land Surveyors

OHIO

Section 29, Jackson Twp.

25 50

SCALE

100

150

200

H & S Civil Engineers and Land Surveyors

913 Fieldstone Court Wapakoneta, Ohio 45895 Phone (419) 738-4758 Fax (419) 739-7631 email: hscivil@bright.net

Ted K. Schnell P.E., P.S. Gregory B. Huber P.E.



02/25/06

SURVEYOR'S DESCRIPTION FOR 5.010 ACRE PARCEL SPLIT

The following described Parcel of land is a part of the West Half of the Southeast Quarter of Section 29, Jackson Township, Town-7-South, Range-4-East, Auglaize County, Ohio, and is more particularly described as follows:

Commencing for reference at a Monument Box (found) located at the Southeast Corner of the Southeast Quarter of said Section 29, Jackson Township;

Thence with a bearing of N. 88°-41'-53" W. along the South Line of the Southeast Quarter of said Section 29, Jackson Township, and the centerline of Minster-Ft. Recovery Road (C.R. 30), for a distance of 1,532.00 feet to a Mag Nail/Shiner (set) and the PLACE OF BEGINNING;

Thence continuing with a bearing of N. 88°-41'-53" W. along the South Line of the Southeast Quarter of said Section 29, Jackson Township, and the centerline of Minster-Ft. Recovery Road (C.R. 30), for a distance of 325.00 feet to a Mag Nail/Shiner (set);

Thence with a bearing of N. 01°-43'-33" E. for a distance of 671.51 feet to an Iron Pin (set), and passing thru an Iron Pin (set) on the Northerly Right-of-Way Line of Minster-Ft. Recovery Road (C.R. 30), at a distance of 30.00 feet;

Thence with a bearing of S. 88°-41'-53" E. and parallel with South Line of the Southeast Quarter of said Section 29, Jackson Township, and the centerline of Minster-Ft. Recovery Road (C.R. 30), for a distance of 325.00 feet to an Iron Pin (set);

Thence with a bearing of S. 01°-43'-33" W. for a distance of 671.51 feet to a Mag Nail/Shiner (set), and passing thru an Iron Pin (set) on the Northerly Right-of-Way Line of Minster-Ft. Recovery Road (C.R. 30), at a distance of 641.51 feet, said Mag Nail/Shiner being the original PLACE OF BEGINNING.

Containing in all 5.010 Acres of land, of which, 0.224 Acre being previously dedicated for highway purposes. The above described Parcel of land is also subject to all other legal easements, reservations, or restrictions, if any, upon said premises. Previous Deed References: DEED VOLUME OR 534, PAGE 1783, Auglaize County Recorder's Office. Bearings were based upon the Auglaize County Engineer's Global Positioning Survey.

PREPARED BY:

Ted K. Schnell Professional Engineer Professional Surveyor