



BEING PART OF THE THE NORTHEAST QUARTER (1/4) OF THE SOUTHWEST QUARTER (1/4)
OF SECTION 19, TOWN 7 SOUTH, RANGE 4 EAST, JACKSON TOWNSHIP, AUGLAIZE COUNTY, OHIO

IN 2008, HEITKAMP ROAD WAS RAISED AT THIS LOCATION AND THE EX. MONUMENT BOX WAS REMOVED. THE AUGLAIZE COUNTY ENGINEER'S OFFICE PLACED A MAG NAIL AT THE CENTER OF SECTION 19 AFTER CONSTRUCTION ENDED IN THE FALL OF 2008. THIS MONUMENTATION WAS USED FOR THIS SURVEY.



P.O. BOX 86
OSGOOD, OHIO 45351
PHONE: (419) 305-3335



Q284

**Survey for
Leon E. & Elaine A. Heitkamp
Tract "A"
15.235 Ac.**

Being part of the Northeast Quarter (1/4) of the Southwest Quarter of Section 19, Town 7 South, Range 4 East, Jackson Township, Auglaize County, Ohio, and described as follows:

Commencing at a Mag Nail Found marking the Center Post of Section 19 and the **TRUE POINT OF BEGINNING**;

Thence South 01°29'58" West along the East line of the Southwest Quarter of Section 19, a distance of one thousand three hundred forty and ninety-three hundredths feet (1340.93') to a 6" Square Wood Post Found, passing a Iron Pin with Cap Set at twenty-five and zero hundredths feet (25.00') and an Iron Pin with Cap Set at one thousand thirty and ninety-three hundredths feet (1330.93');

Thence North 88°50'45" West, a distance of four hundred ninety-four and eighty-eight hundredths feet (494.88') to an Iron Pin with Cap Set;

Thence North 01°29'54" East, a distance of one thousand three hundred forty and ninety-seven hundredths feet (1340.97') to a Mag Nail Set, passing Iron Pins with Caps Set at one thousand fifty and forty-seven hundredths feet (1050.47') and one thousand three hundred fifteen and ninety-seven hundredths feet (1315.97');

Thence South 88°50'28" East along the North line of the Southwest Quarter of Section 19 and the approximate Centerline of Heitkamp Road, a distance of four hundred ninety-four and ninety-one hundredths feet (494.91') to the **TRUE POINT OF BEGINNING** containing 15.235 acres of land more or less.

Said tract being subject to all highways and any other easements or restrictions of record.

Previous Deed Reference: O.R. 140, Page 889

Description based on a survey by Craig W. Mescher Registered Surveyor No. 8237 in March 2009 and is on file with the Auglaize County Engineer's Office.

Q287

**Survey for
Dale J. & Diane M. Wolters
Tract "B"
14.235 Ac.**

Being part of the Northeast Quarter (1/4) of the Southwest Quarter of Section 19, Town 7 South, Range 4 East, Jackson Township, Auglaize County, Ohio, and described as follows:

Commencing at a Mag Nail Found marking the Center Post of Section 19;

Thence North 88°50'28" West along the North line of the Southwest Quarter of Section 19 and the approximate Centerline of Heitkamp Road, a distance of six hundred forty-four and ninety-one hundredths feet (644.91') to a Mag Nail Set and the **TRUE POINT OF BEGINNING**, passing a Mag Nail Set at four hundred ninety-four and ninety-one hundredths feet (494.91');

Thence South 01°29'54" West, a distance of two hundred ninety and fifty hundredths feet (290.50') to an Iron Pin with Cap Set;

Thence South 88°50'28" West, a distance of one hundred fifty and zero hundredths feet (150.00') to an Iron Pin with Cap Set;

Thence South 01°29'54" West, a distance of one thousand three hundred forty and ninety-seven hundredths feet (1050.47') to an Iron Pin with Cap Set;

Thence North 88°50'45" East, a distance of four hundred ninety-four and eighty-eight hundredths feet (494.88') to an Iron Pin with Cap Set;

Thence North 01°29'50" East, a distance of one thousand three hundred forty-one and one hundredths feet (1341.01) to a Mag Nail Set, passing an Iron Pin Found at eight hundred eighteen and twenty-two hundredths feet (818.22') and one thousand sixty-eight and seventy-three hundredths feet (1068.73'), and an Iron Pin with Cap Set at one thousand three hundred twenty-one and one hundredths feet (1321.01');

Thence South 88°50'28" East along the North line of the Southwest Quarter of Section 19 and the approximate Centerline of Heitkamp Road, a distance of three hundred forty-four and ninety-one hundredths feet (344.91') to the **TRUE POINT OF BEGINNING** containing 14.235 acres of land more or less.

Said tract being subject to all highways and any other easements or restrictions of record.

Previous Deed Reference: O.R. 289, Page 200

Description based on a survey by Craig W. Mescher Registered Surveyor No. 8237 in March 2009 and is on file with the Auglaize County Engineer's Office.

Q 288

**Survey for
Dale J. & Diane M. Wolters
Tract "C"
1.000 Ac.**

Being part of the Northeast Quarter (1/4) of the Southwest Quarter of Section 19, Town 7 South, Range 4 East, Jackson Township, Auglaize County, Ohio, and described as follows:

Commencing at a Mag Nail Found marking the Center Post of Section 19;

Thence North 88°50'28" West along the North line of the Southwest Quarter of Section 19 and the approximate Centerline of Heitkamp Road, a distance of four hundred ninety-four and ninety-one hundredths feet (494.91') to a Mag Nail Set and the **TRUE POINT OF BEGINNING**;

Thence South 01°29'54" West, a distance of two hundred ninety and fifty hundredths feet (290.50') to an Iron Pin with Cap Set, passing an Iron Pin with Cap Set at twenty-five and zero hundredths feet (25.00');

Thence North 88°50'28" West, a distance of one hundred fifty and zero hundredths feet (150.00') to an Iron Pin with Cap Set;

Thence North 01°29'54" East, a distance of two hundred ninety and fifty hundredths feet (290.50') to a Mag Nail Set, passing an Iron Pin with Cap Set at two hundred sixty-five and fifty hundredths feet (265.50');

Thence South 88°50'28" East along the North line of the Southwest Quarter of Section 19 and the Centerline of Heitkamp Road, a distance of one hundred fifty and zero hundredths feet (150.00') to the **TRUE POINT OF BEGINNING** containing 1.000 acres of land more or less.

Said tract being subject to all highways and any other easements or restrictions of record.

Previous Deed Reference: O.R. 289, Page 200

Description based on a survey by Craig W. Mescher Registered Surveyor No. 8237 in March 2009 and is on file with the Auglaize County Engineer's Office.

Q289