



Scale 1"=100'

DESCRIPTION

Being a parcel of land in the W½ of the NE¼ of Section 19, T5S, R8E, Wayne Township, Auglaize County, Ohio, more particularly described

Commencing for reference at the monument box at the northwest corner of the NE¼ of Section 19, thence S.89°-04'-55"E. (assumed bearing) on the north line of the NE¼ of Section 19, (centerline S.R. 67), 457.61' to a set Mag nail at the POINT OF BEGINNING of the parcel to be described, thence the following courses;

1. Continue S.89°-04'-55"E. on the north line of the NE1/4 (centerline S.R. 67), 272.31' to a set Mag nail;

rebar at 30.00':

3. S.88°-41'-36"W., 105.83' to a set #5 rebar; 4. S.3°-09'-24"W., 75.57' to a set #5 rebar;

5. S.88°-30'-11"W., 164.27' to a set #5 rebar;

6.N.1*-21'-24"E., 247.61' to the POINT OF BEGINNING, passing over a set #5 rebar at 217.61' on the south R/W of S.R. 67.

The above-described parcel contains 1.327 acres, more or less, subject to all legal highways and easements of record at the time of

Prior O.R. 585, Page 703.

This plat and description is based on a field survey on 11-4-09 by, Bacon & Associates, LLC under direction of Clayton T. Bacon, P.S.

DESCRIPTION

Being a parcel of land in the W½ of the NE¼ of Section 19, T5S, R8E Wayne Township, Auglaize County, Ohio, more particularly described as

Commencing for reference at the monument box at the northwest corner of the NE¼ of Section 19, thence S.89°-04'-55"E. (assumed bearing) on the north line of the NE¼ of Section 19, (centerline S.R. 67), 340.00' to a set Mag nail at the POINT OF BEGINNING of the parcel to be described, thence the following courses;

1. Continue S.89°-04'-55"E. on the north line of the NE¼ (centerline S.R. 67), 117.61' to a set Mag nail;

2.S.1°-21'-24"W., 247.61' to a set #5 rebar, passing over a set #5 rebar at 30.00':

3. N.88°-30'-11"E., 164.27' to a set #5 rebar;

4.N.3°-09'-24"E., 75.57' to a point, passing over a set #5 rebar at

5.N.88°-41'-36°E., 105.83' to a set #5 rebar; 6.S.1°-24'-29°W., 569.93' to a set #5 rebar;

7. S.89°-04'-55"E., 304.00' to a set #5 rebar;

8. S.1°-24'-28"W., 588.31' to a set #5 rebar, being S.30°-29'-58"W., 1.31' from an existing #5 rebar with an ODOT plastic cap;

9. N.89°-08'-48"W. on the south line of the NW1/4 of the NE1/4, 692.74" to a set #5 rebar, being S.40°-46'-39"W., 8.60' from an existing 3"x3" angle iron fence corner post;

10. N.1°-21'-24"E., 1320.08' to the POINT OF BEGINNING, passing over a set #5 rebar on the south R/W line of S.R. 67, 1290.08'.

The above-described parcel contains 14.576 acres, more or less, subject to all legal highways and easements of record at the time of

Prior O.R. 585, Page 703.

This plat and description is based on a field survey on 11-4-09 by, Bacon & Associates, LLC under direction of Clayton T. Bacon, P.S. #6179.



This description and plat is based on an actual field survey performed on 10-30-09, by Bacon & Associates under the direction of Clayton T. Bacon, P.S. #6179

SSOCIATES, N. Eastown Rd., Elida, Ohio 45807 (419) 999-3756 - Fax: (419) 999-2523 ⋖ ळ BACON Tussing \simeq R8E Daniel **T5S**, ಳ Engle 9 Section

Deborah

Hutchison,

 \leq

Ohio

County,

laize

9

Au

ownship

Wayne

RET

W1/2,

Patricia 182-09 60 MSH 11-6jte: