


LEGEND

- A - Set #5 rebar
- B - Set Mag nail
- C - Existing Odot Concrete Monument
Odor Sta. 64+93.09



LINE TABLE		
LINE	BEARING	LENGTH
L1	N68°40'36"W	55.93'
L2	N54°43'52"W	87.82'
L3	N67°53'42"W	15.00'
L4	N78°53'56"W	96.49'
L5	N78°53'56"W	86.88'
L6	N67°53'43"W	76.59'

Curve Data

C~1
 PI Sta. 63+69.35
 Δ = 7°-26'-04"
 R = 1909.86'
 L = 144.16'
 L.C. = N.65°-43'-59"W., 144.12'
 Seg. = 130.67 S.F.

C~2
 Δ = 7°-26'-04"
 R = 5729.58'
 L.C. = N.68°-10'-33"W., 56.10'
 L = 56.10'
 Seg. = 2.57 S.F.



Clayton T. Bacon
 Clayton T. Bacon, Reg. P.S. #6179
 2-10-15

This description and plat is based on an actual field survey performed on 1-16-15, by Bacon & Associates under the direction of Clayton T. Bacon, P.S. #6179

Prepared By
Bacon & Associates, L.L.C.
 750 N. Eastown Rd., Elida, Ohio 45807
 Office: (419) 999-3756 - Fax: (419) 999-2523

Bill Carpenter
 NW1/4, Section 5, T6S, R4E
 St. Marys Township, Auglaize County, Ohio

Revisions:

Drawn: BTB Date: 2-5-15

S-15

BACON & ASSOCIATES, LLC

Engineering and Surveying

750 N. Eastown Road

Phone: (419) 999-3756
FAX: (419) 999-2523

Elida, Ohio 45807

DESCRIPTION (2.000 Acre Parcel)

Being a parcel of land in the NW¼ of Section 5, T6S, R4E, St. Marys Township, Auglaize County, Ohio, more particularly described as follows:

Commencing for reference at a set Mag nail at the P.T. on the centerline of R/W of S.R. 703 at ODOT Sta. 64+93.09. Said point being N.22°-06'-17"E., 30.00' from an ODOT concrete monument marking said point, thence S.67°-53'-43"E. on the centerline of S.R. 703, 372.19' to a set Mag nail at the POINT OF BEGINNING, thence the following courses;

1. N.22°-06'-17"E., 364.35' to a set #5 rebar on the south railroad right of way line, passing over a set #5 rebar at 46.58' on the north right of way line of S.R. 703;
2. S.60°-07'-51"E. on said south railroad right of way line, 252.36' to an existing #5 rebar;
3. S.21°-53'-02"W., 329.98' to a set Mag nail on the centerline of S.R. 703, passing over a set #5 rebar at 284.49';
4. Northwestery on a non-tangential curve to the right on the centerline of S.R. 703, 56.10' to a set Mag nail at the ODOT P.C. Sta. 70+60.51. said curve having a radius of 529.58' and a chord of N.68°-10'-33"W., 56.10';
5. N.67°-53'-43"W. on the centerline of S.R. 703, 195.23' to the POINT OF BEGINNING.


The above-described parcel contains 2.000 acres, more or less, subject to all legal highways and easements of record at the time of survey.

A bearing of N.67°-53'-43"W. was assumed for the centerline of S.R. 703 R/W between the P.T. Sta. 64+93.09 and the P.C. Sta. 70+60.51.

Prior D.V. 56, Page 165

This plat and description is based on a field survey on 01-16-15 by, Bacon & Associates, LLC under direction of Clayton T. Bacon, P.S. #6179.

Clayton T. Bacon
2-10-15



S-112