


87
93

MERCER COUNTY
AUGLAIZE COUNTY
MER-197-(6.53)(6.98)(8.89)
AUG-197-(2.52)

LOCATION PLAN



SECTION 2

CURVE DATA

PI STA. 390+43.64	$\Delta = 52^{\circ}31'10''$ LT.
LS = 300'	E = 221.97'
Ts = 1093.17'	Os = 4.5'
P = 1.96'	K = 149.97'
Xc = 299.81'	Yc = 7.85'
Ac = 43°31'10"	Lc = 1450.65'
Rc = 1909.86'	
Dc = 3°00'	

190~BEGIN P
PART I
+60~S

CENTER TWO
PART II

SEC. 11 T. 5 S. - R. 3 E

STA. 435+72.1
STONE

CENTER TWP.

SEC. 1 T. 5 S. - R. 3 E

PART III

CENTER TWP. SEC. 12 T. 5 S. - R. 3 E.

MERCER
AUGLAIZE

SALEM TWP.
SEC. 7 T. 5 S. - R. 3 E.

SALEM TWP. SEC. 6 T. 5S. - R. 3E.

SALEM TWP.
SEC.32T.4S.-R.4E.

PART IV

SALEM TWP. SEC.5 T.5S.-R.4E.

RESUME PROJECT
HUSSEY

ST-STA. 143+50
143+65

2.4 E. PROJECT ~ STA. 143+
PK ~ STA. 143+65

STA. 165+40.5 ~ STONE
S.B. 1162

4 REFERENCE POINT MONUMENTS
TO BE SET

STATION		DISTANCE FROM		STATION		DISTANCE FROM	
	LT.	RT.			LT.	RT.	
347+00	16'	16'		460+00	20'	20'	
352+00	"	"		465+00	"	"	
369+00	16'	16'		132+50	45'	45'	
373+00	"	"		136+00	60'	60'	
TS379+50.22	"	"	PI	138+90.2	MON	BOX	*
SC382+50.22	"	"		139+00	60'	60'	
1P389+75.78	"	"		143+00	40'	40'	
CS397+01.33	"	"					
ST400+01.33	"	"	*TO BE SET BY CONTRACTOR				

TYPICAL DETAIL FOR LOCATION
OF & AND/OR RIW MONUMENTS
& REFERENCE POINTS TO BE
SET FOR STA. & DISTANCE LT.
& RT. SEE TABLE LEFT.

RECORDED

MERCER COUNTY AUGLAIZE COUNTY

DATE
VOL.
PAGE

DATE _____
VOL. _____
PAGE _____

I HEREBY CERTIFY THAT THIS PLAT IS A TRUE
DELINEATION OF A SURVEY MADE BY THE OHIO
DEPARTMENT OF HIGHWAYS IN 1965.

Carl E. Keyser
CARL E. KEYSOR
REGISTERED SURVEYOR NO 3783

RIW PLAN ~ LOCATION PLAN ~ SHEET 2 OF 8