

CENTERLINE SURVEY PLAT

REC. NO. 5
 DIVISION 5
 STATE OHIO
 PROJECT AUGLAIZE COUNTY
 AUG-703-258

CURVE #1

PI. = 134+97.39
 Δ = 4°22'
 D = 2°00'
 L = 218.34'
 E = 2.08'
 R = 2864.73'
 T = 103.23'

CURVE #2

PI. = 141+18.78
 Δ = 15°45'10"
 D = 7°00'05"
 L = 824.52'
 E = 7.76'
 R = 518.36'
 T = 112.97'

CURVE #3

PI. = 133+77.13
 Δ = 14°56'38"
 D = 4°00'26"
 L = 372.91'
 E = 12.34'
 R = 1423.88'
 T = 187.52'

SCALE IN FEET
 0 100 200 300

CITY OF ST. MARYS
 ST. MARYS TOWNSHIP, T6S R4E
 AUGLAIZE COUNTY, OHIO

N

PROPERTY MONUMENTS

STATION	DIST. FROM	TYPE OF	REFERENCE	REMARKS
LOCATION	LEFT	RIGHT	MONUMENT	
132+11.34	48.70'		2" IRON PIPE	POINT ON R.
132+38.38	29.35'		1/4" IRON BAR	PROP. CORNER
134+73.07	29.15'		CONC. MON.	PROP. CORNER
136+25.43	29.01'		1/4" IRON PIPE	PROP. CORNER
137+31.40	ON E OF SURVEY		RK. NAIL	PROP. LINE @ S
138+28.44	0.14'		R.R. SPIKE	PROP. LINE @ S
138+28.61	0.16'		R.R. SPIKE	PROP. LINE @ E
144+71.62	30.27'		1/4" IRON BAR	PROP. CORNER
147+32.16	ON E OF SURVEY		RK. NAIL	PROP. LINE @ E
148+38.48	ON E OF SURVEY		RK. NAIL	PROP. LINE @ S
148+45.97	30.02'		R.R. SPIKE	PROP. CORNER
149+64.73	1.66'		R.R. SPIKE	PROP. LINE @ C
150+29.60	1.62'		R.R. SPIKE	PROP. LINE @ E
152+06.41	1.60'		R.R. SPIKE	PROP. LINE @ E
156+66.60	33.01'		1" IRON PIPE	PROP. CORNER
157+66.16	33.19'		1/4" IRON PIPE	PROP. CORNER
158+05.97	33.00'		CONC. MON.	PROP. CORNER NE CORNER HILLSDALE 1st
159+38.41	33.24'		1/4" IRON PIN	PROP. CORNER
161+58.45	33.00'		1/4" IRON PIN	PROP. CORNER
162+39.14	33.26'		1/4" IRON PIPE	PROP. CORNER
162+59.35	33.00'		1/4" IRON PIPE	PROP. CORNER

POINTS USED TO ESTABLISH CENTERLINE

STATION	DIST. FROM	REMARKS
LEFT	RIGHT	
150+00	30.00'	STATE R/W MONUMENT FD.
133+48.17	30.00'	STATE R/W MONUMENT FD.
150+00	30.00'	STATE R/W MONUMENT FD.
158+03.87	33.00'	MON. MARKING NE CORNER OF HILLSDALE 1st ADD. FOUND.
162+59.35	33.00'	IRON PIPE @ PROP. CORNER FD.
148+25.68	0	REFERENCE FROM CITY RECORDS

Received June 6 1983
 at 1:26 P.M.
 Received June 6 1983
 Vol. No. 1 Page 69
 #41.30
 Michael L. Weadock

NOTE: THE BEARINGS OF THE CENTERLINE OF S.R. 703 WERE BASED ON THE BEARINGS GIVEN ON THE STATE OF OHIO RIGHT-OF-WAY PLANS FOR S.H. 167 (S.R. 29, S.R. 703) SEC. 11, A: AUGLAIZE COUNTY, DATED, 1933.

RECORDING DATA
 VOL. _____
 PAGE _____
 DATE _____
 I CERTIFY THIS TO BE A TRUE DELINEATION OF THE CENTERLINE OF STATE ROUTE 703 (CELINE RD. - JACKSON ST.) AS SURVEYED BY THE CITY OF ST. MARYS UNDER MY SUPERVISION, AND THAT THE TYPE AND LOCATION OF MONUMENTS FOUND AND PLACED ARE SHOWN CORRECTLY HEREON.
 Michael L. Weadock, P.S. # 6193

CENTERLINE SURVEY PLAT (PROP AUG-703)